

Digital Visual Interface (DVI) is the standard interface for high-performance connection between PCs and flat panel displays, CRT displays, projectors, and HDTV. This video cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). Three analog 30 AWG coaxial lines enable high speed analog transmission.



Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: blue, white.

Please Note: The DVI connector on this cable can only be inserted into a DVI-I interface.

Features & Benefits

Perfect for connecting VGA devices to analog DVI Displays

Supports resolutions up to 1600 x 1200

Use with DVI-I port on display

Available in lengths up to 5m

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120269557	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

Dimensions

Product Length US	9.8 FT	Cable Length	9.8 ft
-------------------	--------	--------------	--------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
-----------------	--------------------------	------------	--------

Video Resolution	UXGA (1600x1200)	Cable Type	Video
Jacket Rating	Standard / Non-Rated	Cable Diameter	7 mm
Adapter Rear	VGA Male	Adapter Front	DVI-A Male
