



This riser rated OM3 laser-optimized multimode (LOMMF) MPO fiber cable is ready for deployment in any multimode 50/125 MTP/MPO network. OM3 is fully backward-compatible with existing OM2 or OM1 systems. This multimode, MPO fiber cable is comprised of 12 fibers or 6 duplex channels within each connector. These high density cables are perfect when you have limited space, making it possible to run a single cable that automatically terminates 12 fibers in one easy plug-in. The fan-out side has 12 LC connectors that are numbered according to the fiber position in the MPO Connector and duplexed together. The push-pull release mechanism for the MPO connector is easy to engage and disengage, its latch design also prevents the plug from snagging when jumper cables are being routed.

Features & Benefits

| | |
|--|--|
| Labeled duplex LC connectors correspond with the fiber pinout on the MPO connector (No guide pins) | Riser rated (OFNR) Jacket |
| 3mm diameter at the MPO side to 2mm on the breakout side | MPO fans out to 12 Fibers with LC connectors |

Specifications

General Info

| | | | |
|--------------------|------------------------|-------------------|-----------|
| Product Line | C2G | Color | Aqua |
| UPC Number | 757120313243 | Country Of Origin | Hong Kong |
| Application Sector | Commercial, Industrial | Type | Cable |

Dimensions

| | | | |
|-------------------|--------|--------------|--------|
| Product Length US | 9.8 FT | Cable Length | 9.8 ft |
|-------------------|--------|--------------|--------|

Technical Information

| | | | |
|------------------------|--|-----------------|--------------------------|
| Fiber Optic Cable Type | MPO, MTP, Multimode, OM3 | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application | Riser Rated | Bend Radius | 45 mm |
| Simplex/Duplex | Full-Duplex | Cable Type | Breakout, Fiber Optic |
| Jacket Rating | FT4 Rated, OFNR Rated | Cable Diameter | 3 mm |
| Adapter Rear | LC Male, LC Male, LC Male, LC Male, LC Male, LC Male | Adapter Front | MPO Male |