



The 8 Ohm 50W Audio Amplifier is the ideal solution for supporting a sound reinforcement system in a classroom, conference room or other environment that requires installation in a plenum space. This amplifier supplies 50 Watts of power, 25 Watts per channel, and is built to an industry standard 8 Ohm design. This amplifier supports many advanced features which make it a perfect fit for most applications

*Noise Reduction*

Audio systems installed in commercial environments are susceptible to noise caused by an electrical ground loop. This will often manifest as a hum or buzz through the system. This amplifier features noise reduction technology on both the 3.5mm and RCA Stereo Audio inputs. This noise reduction eliminates the interference and allows the audio signal to pass through.

*Standby Mode*

After five minutes without a signal, the amplifier will enter standby mode providing energy savings. The amplifier will wake from standby mode automatically when a signal is received.

*Accessory Power Output*

The accessory power output provides 12 Volts DC and 500 mAmps. This makes the amplifier the perfect match for a controller such as the

## Features & Benefits

Reduces noise in commercial environments

Industry standard 8 Ohm design

Designed for installation in Plenum air spaces

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120408802	Country Of Origin	Taiwan, Province Of China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Amplifier		

### Dimensions

Product Width US	4.54 in	Product Height US	1.49 in
Product Length US	4.31 in		

---

## Listing Agencies / 3rd Party Agencies

---

FCC Compliant      Yes

---

## Buy American Act Compliance

---

TAA Compliant      Yes

---

## Technical Information

---

Adapter Rear	3.5mm Microphone Female, RCA Stereo Audio Female	Adapter Front	3.5mm Stereo Female
--------------	--	---------------	---------------------

---