



RapidRun is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Ideal for educational and institutional installations, this wall plate allows VGA video, 3.5mm stereo audio to be run over one runner cable, while the HDMI and USB pass through ports allow for a seamless transition to an in-wall cabling. This wall plate is constructed from aluminum for durability and a long life.

**Please note:** Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate. Due to constraints of available conductors for signal transmission, EDID signals are not supported with this product.

## Features & Benefits

Supports VGA video and Stereo Audio signals over a RapidRun Multi-format runner	Flexible HDMI and USB pigtail for easy installation in a wall box
Compatible with standard double gang wall boxes	Aluminum construction for durability and long life

## Specifications

### General Info

Product Line	C2G	Color	White
UPC Number	757120601463	Country Of Origin	China
Application Sector	Commercial	Warranty Type	Lifetime
Type	Wall Plate		

### Dimensions

Product Width US	4.57 in	Product Height US	4.53 in
------------------	---------	-------------------	---------

### Technical Information

Wire Gauge	24 AWG	Video Resolution	UXGA (1600x1200)
Bend Radius	90 mm	Data Transfer Rate	18 Gbps
Adapter Rear	USB-A Female, RapidRun 15-pin Male, HDMI Female	Adapter Front	USB-A Female, VGA Female, 3.5mm Stereo Female, HDMI Female