



This OM4 Duplex Multimode Fiber Optic Cable is ideal for connecting 40GBase BiDi 10GBaseSR, SFP+ and QSFP+ transceivers for 40 and 10 Gigabit network connections. This cable provides backward compatibility with existing 50/125 equipment and the performance headroom required to support LED and VCSEL laser light sources, and 40 or 10 gigabit Ethernet applications in a datacenter or wiring closet..

## Features & Benefits

Constructed to support OM4 transmission standards

Multimode fiber construction - 50/125 diameter core and cladding

Support for 10 Gigabit and 40 Gigabit Ethernet communication

## Specifications

### General Info

|                    |                        |                   |          |
|--------------------|------------------------|-------------------|----------|
| Product Line       | C2G                    | Color             | Aqua     |
| UPC Number         | 757120009979           | Country Of Origin | China    |
| Application Sector | Commercial, Industrial | Warranty Type     | Lifetime |
| Type               | Cable                  |                   |          |

### Dimensions

|                   |        |              |        |
|-------------------|--------|--------------|--------|
| Product Length US | 3.3 FT | Cable Length | 3.3 ft |
|-------------------|--------|--------------|--------|

### Technical Information

|                        |                |                 |                          |
|------------------------|----------------|-----------------|--------------------------|
| Fiber Optic Cable Type | Multimode, OM4 | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application     | Riser Rated    | Bend Radius     | 10 mm                    |
| Simplex/Duplex         | Duplex         | Cable Type      | Fiber Optic              |

---

|                    |                       |                |                  |
|--------------------|-----------------------|----------------|------------------|
| Jacket Rating      | FT4 Rated, OFNR Rated | Cable Diameter | 2 mm             |
| Data Transfer Rate | 40 Gbps               | Adapter Rear   | LC Male, LC Male |
| Adapter Front      | LC Male, LC Male      | Fiber Size     | 50/125           |

---