



Why run all new cables for RS-232 control of your audio/video system, when you can use this easy adapter? The Velocity RS-232 adapter leverages your DB9 or 3.5mm stereo audio cable to run 3-conductor RS-232 control signals between your control unit and your video display. Fully molded DB9 and 3.5mm connectors provide excellent strain relief. This adapter is ideal for use with computers, projectors, and any control unit/display requiring 3-conductor RS-232 serial control.

Connector 1: DB9 Male
 Connector 2: 3.5mm Male

Please Note: Not all serial control methods are supported by this adapter. This product is intended only for use with 3-wire RS-232 control cables with common ground (pin 5), transmit data (pin 3), and receive data (pin 2). For the exact pinout of your audio/video equipment, please contact your RapidRun sales representative for assistance, or call customer service at 1-800-506-9607.

Features & Benefits

Adapts a DB9 connection to a 3.5mm connection

Allows for 3-conductor RS-232 control signals between your control unit and your video display

Fully molded DB9 and 3.5mm connectors provide excellent strain relief

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120024446	Country Of Origin	Vietnam
Features	RS232	Application Sector	Commercial, Industrial, Residential
Warranty Type	Lifetime	Type	Adapter, Cable

Dimensions

Product Length US	1.5 FT	Cable Length	1.5 ft
-------------------	--------	--------------	--------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Cable Type	Adapter, Serial
-----------------	--------------------------	------------	-----------------

Jacket Rating

Standard / Non-Rated

Adapter Rear

3.5mm Stereo Male

Adapter Front

DB9 Male
