



For fast Ethernet and Gigabit computer networks that require bandwidthintensive voice, data, or video distribution applications. Meets all Cat6 TIA/EIA standards, and drastically reduces both impedance and structural return loss (SRL). Each of the individual pairs is bonded together to help maintain the twist-spacing throughout the line right up to the termination point. Constructed from high quality copper cable, this design minimizes Near-End Crosstalk (NEXT) levels. Available in a variety of colors to easily color-code your network installation.

Features & Benefits

Designed for network adapters, hubs, switches, routers, HDBaseT applications and more

Meets all Cat6 TIA/EIA requirements for supporting a wide variety of applications

Available in a variety of colors to color-code a network

Supports 10 Gigabit networks up to 180ft for fast data transmission and maximum performance and supports 1 Gigabit up to 328ft

Constructed with unshielded twisted pair (UTP) wires, designed to counter EMI, RFI, and crosstalk

Specifications

General Info

| Product Line | C2G | Color | Blue | |
|-----------------------|---------------------------|--------------------|--|--|
| UPC Number | 757120040941 | Country Of Origin | Vietnam | |
| Features | PoE (Power Over Ethernet) | Application Sector | Commercial, Industrial, Residential | |
| Warranty Type | Lifetime | Туре | Cable | |
| Dimensions | | | | |
| Product Length US | 10.0 FT | Cable Length | 10 ft | |
| Technical Information | | | | |
| Jacket Material | PVC (Polyvinyl Chloride) | Wire Gauge | 24 AWG | |
| | | | | |

| Cable Type | Ethernet Patch Cable, Unbooted, Unshielded (UTP) | Jacket Rating | Standard / Non-Rated |
|----------------|---|---------------|----------------------|
| Cable Diameter | 6 mm | Adapter Rear | RJ-45 Male |
| Adapter Front | RJ-45 Male | | |