



This PCI bus 8-port serial board, with a fan-out (octopus) cable, configures 8 COM ports on the faster PCI bus, at data rates up to 115.2 kbps. It is an extremely dependable communication solution for ISPs or any type of RAS system that does not deal with an overwhelming amount of traffic. Each port includes integrated 16-byte FIFO buffer with software-configurable Tx/Rx triggers.

All eight ports share one PCI bus IRQ, even when accessed simultaneously, and thus saves valuable resources for other expansion cards. The first four serial ports have all of the standard serial signals, while the the last four serial ports do not include the Ring Indicator (RI) input. With easy plug-and-play installation, the Lava Octopus-550 automatically selects the next available IRQ and COM address; just plug it in and go!

Features & Benefits

Allows for dependable communication for ISPs or any type of RAS system

Specifications

General Info

Product Line	C2G	Color	Silver
UPC Number	757120268062	Country Of Origin	Canada
Application Sector	Commercial, Industrial, Residential	Warranty Type	Lifetime
Type	Accessory		

Buy American Act Compliance

TAA Compliant	Yes
---------------	-----

Technical Information

Adapter Front	DB9 Male, DB9 Male, DB9 Male, DB9 Male, DB9 Male, DB9 Male, DB9 Male, DB9 Male
---------------	---
