



Digital Visual Interface (DVI) is the standard interface for high-performance connection between PCs and flat panel displays, CRT displays, projectors, and HDTV. This video cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). Three analog 30 AWG coaxial lines enable high speed analog transmission.

Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: blue, white.

Please Note: This DVI-A connector is compatible with a DVI-I port only and not a DVI-D port.

Features & Benefits

Connect to an existing VGA cable for extra distance to a DVI monitor

Tri-shielded for use in high EMI environments

Available in lengths up to 7.5m

Specifications

General Info

Product Line	C2G	UPC Number	757120275909
Country Of Origin	China	Application Sector	Commercial, Residential
Warranty Type	Lifetime	Type	Cable

Dimensions

Product Length US	6.6 FT	Cable Length	6.6 ft
-------------------	--------	--------------	--------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
Video Resolution	QXGA (2048x1536)	Cable Type	Extension, Video

Jacket Rating

Standard / Non-Rated

Cable Diameter

7 mm

Adapter Rear

VGA Female

Adapter Front

DVI-A Male
