



Cost-effective solution that provides high bandwidth and transmission rates over longer distances. With LC to SC termination, this high quality fiber optic patch cable is specifically designed for gigabit ethernet applications. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 9/125 Single-mode fiber, immune to electrical interference.

## Features & Benefits

Pull-proof PVC jacket provides immunity to electrical interference Single-Mode fiber available in LC, SC, and ST connectors  
 Available in lengths up to 30m

## Specifications

### General Info

Product Line	C2G	Color	Yellow
UPC Number	757120291909	Country Of Origin	China
Application Sector	Commercial, Industrial	Warranty Type	Lifetime
Type	Cable		

### Dimensions

Product Length US	3.3 FT	Cable Length	3.3 ft
-------------------	--------	--------------	--------

### Technical Information

Fiber Optic Cable Type	OS2, Single-Mode	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Riser Rated	Bend Radius	50 mm
Simplex/Duplex	Duplex	Cable Type	Fiber Optic

---

Jacket Rating	FT4 Rated, OFNR Rated	Cable Diameter	1.8 mm
Adapter Rear	SC Male	Adapter Front	LC Male
Fiber Size	9/125		

---