

One component of a complete solution that, when paired with a receiver (sold separately), conquers USB length limits. This solution extends the signal of a USB device to a host computer up to 150 feet, enabling you to place your USB projector, camera, printer, web cam, hub or other USB device exactly where you want it! Our USB superbooster wall plate is powerful yet simple, with no drivers to install or special software required. It's also compatible with any computer that supports USB.

The overall plug-and-play solution consists of this wall plate transmitter, and your choice of a compatible receiver that is sold separately: the 1-port dongle (#29350 or #29353), the 2-port wall plate (#29345), the 2-port dongle (#29346) or the 4-port dongle (#29347). Customize the configuration to your specific needs! This versatility is ideal for applications where you need more than one receiving USB device, or when you need a receiving dongle instead of a receiving wall plate.



The complete solution is connected via a standard Cat5, Cat5E, or Cat6 UTP cable (not included) that provides easy in-wall installation. This delivers a clean, finished look important for homes, classrooms, offices and anywhere you don't want visible cables lying around. Use pre-terminated network cables, or pull unterminated cable and use the included toolless IDC RJ45 connector to terminate your own cable. Because the USB superbooster wall plate is bus-powered, no external power source is required. Compliant with USB specification 1.1.

Please Note: The power demands of devices such as external drives and USB hubs may require the use of external power for proper operation.

Note: If the USB signal is being extended to support an interactive whiteboard, then we recommend using our product

Features & Benefits

| | |
|---|---|
| Extends a USB 1.1 signal up to 150ft over category cables | Allows for flexible positioning of USB peripherals |
| Transmitter is built into a wall plate | Pair with a wall plate or dongle receiver for complete solution |
| Patented, Patent No. US 7,741,562 | |

Specifications

General Info

| | | | |
|--------------|--------------|-------------------|-------|
| Product Line | C2G | Color | White |
| UPC Number | 757120293446 | Country Of Origin | China |

| | | | |
|--------------------|-------------------------|---------------|--------|
| Application Sector | Commercial, Residential | Warranty Type | 5-Year |
|--------------------|-------------------------|---------------|--------|

| | |
|------|---|
| Type | Active Device, Extender, Transmitter, Wall Plate |
|------|---|

Dimensions

| | | | |
|------------------|---------|------------------|---------|
| Product Width US | 1.31 in | Product Depth US | 1.34 in |
|------------------|---------|------------------|---------|

| | |
|-------------------|---------|
| Product Height US | 4.13 in |
|-------------------|---------|

Technical Information

| | | | |
|-----------------|---|--------------------|---------|
| Number of Gangs | 1 | Data Transfer Rate | 12 Mbps |
|-----------------|---|--------------------|---------|

| | | | |
|--------------|--------------|---------------|--------------|
| Adapter Rear | RJ-45 Female | Adapter Front | USB-B Female |
|--------------|--------------|---------------|--------------|
