



Make MTP/MPO your choice for high density fiber networks; it's specifically designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications. Save time and money with MTP/MPO's increased ease of installation - simply pull one cable rather than twelve. Each MTP/MPO fiber assembly consists of twelve 62.5/125µm single-mode fibers under one PVC (OFNR-rated) jacket.

With our MTP/MPO, it's possible to run a single cable that automatically terminates twelve fibers in one easy plug-in. Plus, the small form factor of an MTP/MPO connector provides a higher port density. With its push-pull release mechanism, the MTP/MPO connector is easy to engage and disengage. Plus, its latch design prevents the plug from snagging when jumper cables are being routed. Straight-through pinning; immune to electrical interference.

**Please Note:** MTP/MPO is a registered trademark of US Conec Ltd. Attenuation testing performed in accordance with EIA/TIA-455-171A.

## Features & Benefits

Designed for fast ethernet, fiber channel, ATM and gigabit ethernet applications

## Specifications

### General Info

Product Line	C2G	Color	Orange
UPC Number	757120314127	Country Of Origin	Hong Kong
Application Sector	Commercial, Industrial	Warranty Type	Lifetime
Type	Cable		

### Dimensions

Product Length US	16.4 FT	Cable Length	16.4 ft
-------------------	---------	--------------	---------

### Technical Information

Fiber Optic Cable Type	MTP, Multimode, OM1	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Riser Rated	Bend Radius	45 mm
Cable Type	Fiber Optic	Jacket Rating	FT4 Rated, OFNR Rated
Cable Diameter	3 mm	Data Transfer Rate	1 Gbps
Adapter Rear	MPO Female	Adapter Front	MPO Female

---

Fiber Size

62.5/125

---