



This OM3 Duplex Multimode Fiber Optic Cable is ideal for connecting 10GBase-SR, 10GBase-LRM, SFP+ and QSFP+ transceivers for 10 gigabit network connections. This cable has a OFNP-rated jacket allowing it to be used in a plenum application. This cable also provides backward compatibility with existing 50/125 equipment and the performance headroom required to support LED and VCSEL laser light sources, and 10 gigabit ethernet applications.

Features & Benefits

| | |
|----------------------------------|--|
| OM3 - 50µm core | Designed to support 10GBase-SR and 10GBase-LRM ports and equipment |
| Supports 2000MHz km EMB at 850nm | OFNP - Plenum rated jacket |

Specifications

General Info

| | | | |
|--------------------|------------------------|-------------------|----------|
| Product Line | C2G | Color | Aqua |
| UPC Number | 757120362401 | Country Of Origin | China |
| Application Sector | Commercial, Industrial | Warranty Type | Lifetime |
| Type | Cable | | |

Dimensions

| | | | |
|-------------------|---------|--------------|-------|
| Product Length US | 32.8 FT | Cable Length | 33 ft |
|-------------------|---------|--------------|-------|

Technical Information

| | | | |
|------------------------|----------------------|-----------------|--------------------------|
| Fiber Optic Cable Type | Multimode, OM3 | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application | Plenum Rated | Bend Radius | 50 mm |
| Simplex/Duplex | Duplex | Cable Type | Fiber Optic |
| Jacket Rating | CMP Rated, FT6 Rated | Cable Diameter | 1.8 mm |
| Data Transfer Rate | 10 Gbps | Adapter Rear | LC Male |
| Adapter Front | LC Male | Fiber Size | 50/125 |