

C2G 35ft (10.7m) Pro Series Single Link DVI-D™ Digital Video Cable M/M - In-Wall CL2-Rated Part No. CG-41234



The new Pro Series commercial grade CL2 cables offer true digital performance while meeting the highest standards in building code requirements for in-wall installations. Available for HDMI®, DVI and DVI+3.5mm audio signals, these cables can meet the demands of virtually any commercial installation.

By supporting resolutions of 1080p for displays and up to 1920 x 1200 pixels for computers, and with lengths ranging from 6 to 50 feet, the Pro Series is the ideal connectivity solution for A/V equipment used in classrooms or conference rooms. 24k gold-plated connectors prevent metal corrosion, resulting in the optimal signal transfer for the highest picture and sound quality. Shielded 24AWG copper conductors protect against EMI and RFI to ensure uninterrupted performance. high quality materials and construction, along with rigorous factory testing and a full lifetime warranty, guarantee long-term, dependable performance.

*CL2 is equivalent to FT4 rating in Canada, while CMP is equivalent to FT6.

Please Note: Does not support analog video; only supports digital video signal.

Features & Renefits

Features & Benefit	ts						
In-wall, CL2-rated	Supports up to a 1920x1200 resolution						
Gold plated connectors	24 AWG conductor construction						
Specifications							
General Info							
Product Line	C2G	Color	Black				
UPC Number	757120412342	Country Of Origin	China				
Application Sector	Commercial, Residential	Warranty Type	Lifetime				
Туре	Cable						
Dimensions							
Product Length US	35.0 FT	Cable Length	35 ft				
Technical Information							
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	24 AWG				
Video Resolution	WUXGA (1920x1200)	Jacket Application	In-Wall Rated				
Cable Type	Video	Jacket Rating	CL2 Rated, FT4 Rated				
Cable Diameter	8.35 mm	Adapter Rear	DVI-D Single Link Male				

DVI-D Single Link Male)VI-	-D	Sina	le	Link	Mal	.e
------------------------	--	------	----	------	----	------	-----	----