

C2G 1.6ft (0.5m) Mini-SAS HD to Mini-SAS HD Cable

Part No. CG-54247



Connect storage area network (SAN) devices, hard drives, or other SAS interface devices with this SFF-8644 to SFF-8644 Mini-SAS cable HD. This cable is designed to meet the rigors of the next generation high-performance networks, servers, workstations and desktops, supporting data transfer rates of up to 12 Gbps. Each cable is engineered to utilize the optimal wire gauge and constructed of silver plated solid copper to carry full bandwidth over the entire length of the cable. The focus on quality and performance ensures that the 12Gbps data transfer speed is available to each storage device.

Features & Benefits

Constructed with 24AWG conductors to optimally support the distance between storage devices

Supports data transfer speeds up to 12Gbps

Built with silver plated solid copper conductors

| Specifications | | | | | |
|---------------------------------------|-------------------------|-------------------|----------|--|--|
| General Info | | | | | |
| Product Line | C2G | Color | Black | | |
| UPC Number | 757120542476 | Country Of Origin | China | | |
| Application Sector | Commercial, Residential | Warranty Type | Lifetime | | |
| Туре | Cable | | | | |
| Dimensions | | | | | |
| Product Length US | 1.6 FT | Cable Length | 1.6 ft | | |
| Listing Agencies / 3rd Party Agencies | | | | | |
| CE Certified | Yes | | | | |
| | | | | | |

Technical Information

| Jacket Material | Flexible PVC | Bend Radius | 90 mm |
|-----------------|---------------------------|---------------|----------------------|
| Cable Type | Direct Attach Cable (DAC) | Jacket Rating | Standard / Non-Rated |
| Cable Diameter | 7.75 mm | Adapter Rear | Mini SAS HD |
| Adapter Front | Mini SAS HD | | |