



Send a video signal from a tablet, laptop computer, or another source device with a DisplayPort output port to a projector, monitor, or HDTV with an HDMI, DVI or VGA input port. This compact all-in-one converter is an ideal solution for use in schools, conference rooms, or other work spaces that may utilize assorted displays with varying inputs in multiple rooms throughout a building.

#### On The Go Enhanced

Be prepared for any meeting, presentation, or event with the full confidence that you have the right connections in an ultra-compact design. The DisplayPort to HDMI, VGA, or DVI adapter allows you to connect a DisplayPort equipped laptop or tablet to a projector, monitor, or HDTV with an HDMI, VGA, or DVI input port. The compact design of this adapter converter makes it a perfect fit for BYOD (Bring Your Own Device) applications in education or corporate environments.

#### Straightforward Install

This simple plug and play adapter converter does not require drivers for install and the device is powered through DisplayPort bus power, so no additional power adapters are needed.

#### Port Protection

The dongle-style adapter converter reduces strain on the video port. The cable between the DisplayPort connection and the adapter converter provides strain relief that protects the port from strain damage as cords are moved.

Note: This adapter converter will output signal to one video port at a time. This adapter converter is not designed to output multiple video signals simultaneously.

## Features & Benefits

Convert DisplayPort to HDMI, VGA, or DVI

VGA — 1920 x1080 at 60Hz

HDMI — 3840 x 2160 at 30Hz

3 Year Warranty

Support resolutions up to:

DVI — 1920 x1080 at 60Hz

Dongle style adapter reduces strain on ports

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120543404	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	5-Year

Type	Active Device, Adapter, Converter		
Dimensions			
Product Width US	3.55 in	Product Height US	0.64 in
Product Length US	2.78 in		
Listing Agencies / 3rd Party Agencies			
CE Certified	Yes	FCC Compliant	Yes
Technical Information			
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	32 AWG
Video Resolution	1080p, 4K, 4K 30Hz	Bend Radius	12 mm
Jacket Rating	Standard / Non-Rated	Cable Diameter	5.5 mm
Data Transfer Rate	18 Gbps	Adapter Rear	DVI Female, HDMI Female, VGA Female
Adapter Front	DisplayPort Male	Voltage	30.0 V