



C2G 8in Mini DisplayPort™ Male to VGA + Audio Female Active Adapter Converter - Black

Part No. CG-54683

The Mini DisplayPort Male to VGA + Audio Female Active Adapter Converter allows you to connect the Mini DisplayPort or Thunderbolt™ 2 output of a PC or Mac® to a projector or display which accepts a VGA input and audio input with a 3.5mm AUX port # making it an ideal solution for the office, work space applications, or home use. This adapter is a perfect accessory for Microsoft® Surface® products and other leading laptops.



This active adapter provides a simple and convenient solution that converts the Mini DisplayPort signal to an analog VGA video and stereo audio signal. For added convenience, this adapter includes a USB A to Micro-B cable for required power and a 3.5mm AUX stereo audio output for audio.

This adapter is a simple plug and play solution and carries an active video signal, supporting high-definition resolutions up to 1920 x 1200, allowing it to deliver high quality video image and audio to the connected display.

Discover more connectivity solutions for the [Microsoft Surface](#)

Features & Benefits

VGA resolutions up to 1920 x 1200	3.5mm AUX port for audio
Active Mini DisplayPort to VGA conversion	USB power with included cable
Plug and Play — no driver required	Compatible with the Microsoft® Surface® Book 2, Surface Pro 6, Surface Laptop 2, and other leading laptops

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120546832	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	5-Year
Type	Active Device, Adapter, Converter		

Dimensions

Product Length US	8.0 in	Cable Length	0.67 ft
-------------------	--------	--------------	---------

Listing Agencies / 3rd Party Agencies

FCC Compliant	Yes
---------------	-----

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	32 AWG
Video Resolution	1080p, WUXGA (1920x1200)	Jacket Rating	Standard / Non-Rated
Cable Diameter	5.2 mm	Data Transfer Rate	10.8 Gbps
Adapter Rear	VGA Female, USB Micro-B Female, 3.5mm Stereo Female	Adapter Front	Mini DisplayPort Male
Voltage	30.0 V		
