



C2G Performance Series Ultra Flexible High Speed HDMI Cables extend signals over a high-performance HDMI cable and support HDMI audio and video features including 4K Ultra HD.

These cables are perfect for connecting a wide variety of devices from computers to projectors and monitors, AV presentation furniture, or in-wall applications requiring high speed HDMI features and video resolutions up to 4K (4096 x 2160) at 60Hz - perfect for conference rooms, classrooms, houses of worship, and other commercial installations.

This Ultra Flexible High Speed HDMI Cable was designed for installations in tight spaces and offers commercial grade connectors that feature compact overmolding for high density environments, integrated finger grips on the top, bottom, and sides, for easy insertion and removal, and the gripping connector shell has 2x greater port retention to keep your devices connected. The gold plated connectors on the cable allow for better shielding, increased electrical conductivity, and durability.

## Features & Benefits

Supports all HDMI 2.0 features including resolutions up to 4K (4096 x 2160) at 60Hz, which means higher quality video for viewing your screen content	In-wall (CMG/FT4) rated jacket, so you can safely run the cable inside of a wall and have a clutter-free, clean look
Integrated finger grips on the connectors for easy insertion and removal	Gripping connector shell for 2x greater port retention
Gold-plated connectors for increased electrical conductivity and enhanced durability	Supports CEC extensions for control of consumer electronics devices through a single control point
Backed by a Lifetime Warranty for peace of mind	

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120103738	Country Of Origin	China
Features	Gripping Connectors	Application Sector	Commercial, Residential
Warranty Type	Lifetime	Type	Cable

### Dimensions

Product Length US	1.0 FT	Cable Length	1 ft
-------------------	--------	--------------	------

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Video Resolution	4K
Jacket Application	In-Wall Rated	Bend Radius	48 mm
Cable Type	High Speed HDMI, Ultra-Flexible, Video	Jacket Rating	CMG Rated, FT4 Rated
Cable Diameter	6 mm	Data Transfer Rate	18 Gbps
Signal	HDMI 2.0	Adapter Rear	HDMI Male

---

Adapter Front

HDMI Male

Operating Temperature

-20°-75°C

---

Storage Temperature

-10° - 55° C

---