

C2G 20ft (6.1m) C2G Performance Series Ultra Flexible Active High Speed HDMI Cable - 4K 60Hz In-Wall, CMG (FT4) Rated

C2G Performance Series Ultra Flexible Active High Speed HDMI Cables extend HDMI signals over a high performance active HDMI cable and support HDMI audio and video features including 4K Ultra HD.



These cables are perfect for connecting a wide variety of devices from computers to projectors and monitors, AV presentation furniture, or in-wall applications requiring high speed HDMI features and video resolutions up to 4K (4096×2160) at 60Hz -perfect for conference rooms, classrooms, houses of worship, and other commercial installations.

This Ultra Flexible Active High Speed HDMI Cable was designed for installations in tight spaces and offers commercial grade connectors that feature compact overmolding for high density environments, integrated finger grips on the top, bottom, and sides, for easy insertion and removal, and the gripping connector shell has 2x greater port retention to keep your devices connected. The gold plated connectors on the cable allow for better shielding, increased electrical conductivity, and durability.

C2G Performance Series Ultra Flexible Active High Speed HDMI Cable amplifies the signal from the source and sends it longer distances without degrading that signal. Active HDMI cables can only run in one direction - connect the source end to the source and the display end to your display. The connectors are conveniently labeled for source and display, so there is no confusion with this directional cable. The source connector end even has a tag on the cable as an extra reminder. Lastly, this fully-functional, high bandwidth cable has been tested to perform at industry standards and is backed by a lifetime warranty.

Features & Benefits

Supports all HDMI 2.0 features including resolutions up to 4K (4096 x 2160) at 60Hz, which means higher quality video for viewing your screen content

Integrated finger grips on the connectors for easy insertion and removal

Gold plated connectors for increased electrical conductivity and enhanced durability

Supports CEC extensions for control of consumer electronics devices through a single control point $% \left(1\right) =\left(1\right) \left(1\right) \left($

In-wall (CMG/FT4) rated jacket, so you can safely run the cable inside of a wall and have a clutter free, clean look

Gripping connector shell for 2x greater port retention

Directional cable with source connector labeled and tagged to easily differentiate from the labeled display connector

Backed by five-year warranty

Specifications

120103813 oping Connectors	Application Sector	Black China Commercial, Residential Active Device, Cable
oping Connectors	Application Sector	Commercial, Residential
		·
ear	Туре	Active Device, Cable
) FT	Cable Length	20 ft
C (Polyvinyl Chloride)	Wire Gauge	30 AWG
	Jacket Application	In-Wall Rated
mm	Cable Type	High Speed HDMI, Ultra-Flexible, Video
G Rated, FT4 Rated	Cable Diameter	6 mm
Gbps	Signal	HDMI 2.0
MI Male	Adapter Front	HDMI Male
m G	(Polyvinyl Chloride) m Rated, FT4 Rated	(Polyvinyl Chloride) Wire Gauge Jacket Application Cable Type Rated, FT4 Rated Cable Diameter Signal

Operating Temperature -40°-85°C Storage Temperature -10° - 55° C