



C2G Performance Series HDMI Cables are perfect for connecting a wide variety of devices from computers to projectors and monitors, AV presentation furniture, or in-wall applications requiring HDMI features and video resolutions from 1080p, up to 4K — perfect for conference rooms, classrooms, churches, and other commercial installations.

These HDMI Cables offer commercial-grade connectors that feature compact overmolding for high density environments, integrated finger grips on the top, bottom, and sides for easy insertion and removal. The gripping connector shells have 2x port retention to keep your devices connected. The gold-plated connectors on the cables allow for better shielding, increased electrical conductivity, and durability.

These HDMI Cables support the updated library of Consumer Electronic Control (CEC) commands, allowing communication between devices connected through the HDMI ports. Lastly, these fully functional, high bandwidth cables have been tested to perform at industry standards and are backed by a lifetime warranty.

Features & Benefits

Supports resolutions up to 4K (4096 x 2160) at 30hz 4:4:4, which means higher quality video for viewing your screen content	In-wall (CMG/FT4) rated jacket, so you can safely run the cable inside of a wall and have a clutter free, clean look		
Integrated finger grips on the connectors for easy insertion and removal	Gripping connector shell for 2x greater port retention		
Gold plated connectors for increased electrical conductivity and enhanced Gold plated connectors for increased electrical conductivity a durability enhanced durability			

Backed by a Lifetime Warranty for peace of mind

Specifications

General Info

Product Line	C2G	Color	Black		
UPC Number	757120103899	Country Of Origin	China		
Features	Gripping Connectors	Application Sector	Commercial, Residential		
Warranty Type	Lifetime	Туре	Cable		
Dimensions					
Product Length US	50.0 FT	Cable Length	50 ft		
Listing Agencies / 3rd Party Agencies					
CE Certified	Yes				
Technical Information					
Jacket Material	PVC (Polyvinyl Chloride)	Video Resolution	1080p		

Jacket Application	In-Wall Rated	Bend Radius	95 mm
Cable Type	Standard Speed HDMI, Video	Jacket Rating	CMG Rated, FT4 Rated
Data Transfer Rate	4.4 Gbps	Adapter Rear	HDMI Male
Adapter Front	HDMI Male	Operating Temperature	-20°-75°C
Storage Temperature	-10° - 55° C		