

Legrand keyed LC fiber adapter panels are available in configurations that are keyed on the front only (user’s side)



## Features & Benefits

**Unique Key and Color Options:** Up to thirteen unique keying options/colors for a wide range of network security systems, easy identification and network management.

**Keyed front or Rear:** Keyed LC adapters have the option to be keyed in the front only (user’s side) or on both sides (user’s and technician’s) depending on the security requirements. Internal keying feature prevents tampering

**Various Footprint Options:** Keyed workstation adapter modules are available for TracJack® and High Density Jack (HDJ) style Face plates and surface mount boxes for complete system design flexibility.

**Compatibility:** All Legrand keyed LC fiber products are engineered to be compatible with other Legrand products to provide an end to end, data center to desktop solution.

## Specifications

### General Info

|               |              |                    |                                      |
|---------------|--------------|--------------------|--------------------------------------|
| Product Line  | C2G          | Color              | Black                                |
| UPC Number    | 757120298861 | Country Of Origin  | China                                |
| Features      | Color-Coded  | Application Sector | Commercial, Residential              |
| Warranty Type | 5-Year       | Type               | Active Device, Adapter, Adapter Ring |

### Technical Information

|                     |  |                       |   |
|---------------------|--|-----------------------|---|
| Jacket Material     | PVC (Polyvinyl Chloride)                           | Video Resolution      | 1080p, 4K, 4K 30Hz, 4K 60Hz   |
| Cable Type          | Adapter, Flexible                                  | Adapter Rear          | Lightning Male, USB-C Male, DisplayPort Male, Mini DisplayPort Male |
| Adapter Front       | HDMI Female, HDMI Female, HDMI Female, HDMI Female | Operating Temperature | 0°-40°C   |
| Storage Temperature | -10° - 60° C                                       |                       |   |