

The Patented (US 11,444,419 B2) Universal 4K HDMI Dongle Adapter Ring is the perfect addition to conference rooms, huddle spaces, lecture halls, or classroom sure that anyone can connect.

Choose from the dropdown boxes on the right hand side to browse and configure the perfect combination of adapters! Customized pull tabs are available for a purchase quantity of 250 units. Don't see what you're looking for, please reach out to our custom team to gain additional assistance.

Looking to expand a current HDMI Adapter Ring Setup? Check out our [Individual HDMI Adapter](#) page to see what you might be missing.

**Dongle Style Adapter**

It can be awkward when connecting an adapter to a smaller laptop or tablet. The adapter may not line up correctly, causing the computer to shift or not set flat on the dongle style adapter gives more flexibility, allowing for better placement when connecting to thin or lighter weight laptops.

**Color Coded Adapters**

Each adapter is color-coded with a band that saves time and frustration by making it easy to identify the adapter you need quickly.

**Pre-Mounted HDMI Cable Included**

The included pre-mounted C2G Performance Series Premium HDMI cable allows this adapter ring to be utilized right out of the box to the in-room HDMI display. adapter ring slides to the HDMI connector when needed and out of the way when not in use, reducing strain on the HDMI cable and clutter on the tabletop. The stopper fits on HDMI cables from 5mm to 10mm in diameter and prevents the adapters from sliding too far down the cable.

**Additional Technical Specifications**

**HDMI Cable Specs**

- Supports HDMI Resolutions up to 4K 60Hz, 4:4:4, 18Gbps
- Jacket Color: Black, PVC Molding

**Dongle Adapter Specs**

**Signal Specifications**

- USB Type-C to HDMI Dongle: 100% Functional Test at 4K/60Hz/4:4:4 Resolution with Standard AV Test Equipment
- DisplayPort to HDMI Dongle: 100% Functional Test at 4K/30Hz Resolution with Standard AV Test Equipment
- Mini DisplayPort to HDMI Dongle: 100% Functional Test at 4K/30Hz Resolution with Standard AV Test Equipment

**Electrical Specifications**

- Rating: Temp 80°C; Voltage 30V
- Conductor Resistance: At 20°C Max 32AWG: mDP/DP: 588.85 OHMS/KM; USB-C: 588 OHMS/KM; 24AWG: 86 OHMS/KM
- Insulation Resistance: mDP/DP: 10M OHMS/KM Min at 20°C DC 500V
- Insulation Resistance: USB-C: PP/HD-PE DC 500V 100M OHMS/KM Min at 20°C
- Dielectric Strength: AC 500V/1 Minute No Breakdown

**Physical Specifications**

- Operating Temperature: 0°C - 40°C (0% - 90%RH)
- Storage Temperature: -10°C - 60°C (0% - 90%RH)
- mDP/DP Minimum Bend Radius: R52mm
- USB-C Minimum Bend Radius: R45mm
- Cables Jacket Rating: VW-1
- Tensile Strength: Unaged: 1500PSI Min, Aged: 70% Min

**Physical Characteristics**

- HDMI Female: Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black with PCB, Shell: SPCC, Gold Plated
- USB Type-C Male (Green Band): Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black, Shell: Gold Plated
- DisplayPort Male (Red Band): Solder Type, Contacts: Gold Flash, Housing: LCP Black, Shell: Gold Plated (with Latches)
- Mini DisplayPort Male (Yellow Band): Solder Type, Contacts: Gold Flash, Housing: LCP Black, Shell: Gold Plated
- All Hoods: Molded Black PVC
- PC Eyelet: 17.8x4.7x2.6mm, Black, Material: PC
- Pull Tab: 80x25x2mm, Material: Polyester, Black Background, White Text, with Black Eyelet
- Universal Mounting Bracket: 85x65x1.2mm, Material: C.R.S. Rigidity: 1/4H, Color: Black
- Product is CE marked and conforms to 2011/65/EU ROHS 2



**Features & Benefits**

Adapters support up to a 4K video resolution, so meeting attendees will be able to see the displayed content for improved comprehension and detailed decision making

Dongle style adapter, allowing for more flexibility when connecting to a laptop or tablet

Adapters are color coded, so no more frustration trying to find the adapter that you typically use for your laptop

Backed by a Lifetime Warranty for peace of mind

Patent Number US 11,444,419 B3

**Specifications**

**General Info**

Product Line	C2G	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime

**Dimensions**

Cable Length	6 ft
--------------	------

---

**Technical Information**

---

Video Resolution	4K 60Hz	Jacket Rating	VW-1
Data Transfer Rate	18 Gbps	Operating Temperature	0°-40°C
Voltage	0 to 30 V	Insulation Material	PVC (Polyvinyl Chloride)
Storage Temperature	-10° - 60° C		

---