



Our complete line of HD15 to 5BNC adapter cables are perfect for switches, HDTVs, projectors and test equipment in conference rooms, classrooms and auditoriums setups. Eliminate the need to reinstall cable by adapting the existing cable to match the inputs or outputs of your application.

This cable is constructed from premium quality 75 Ohm 28AWG mini coax wire to ensure a crisp monitor image. Low loss 75 Ohm impedance and polyethylene dielectric provide an accurate picture resolution and color. Each wire is shielded with 85% copper braid that is soldered 360° to the connector shell to create a shielding solution for a vivid, noise-free image.

First letter of each monitor signal type indicated on the five separated BNC connectors provides easy identification of red, green, and blue leads with horizontal and vertical sync. Fully molded connectors provide excellent strain relief to keep your cable intact.

Features & Benefits

- Adapt existing cables to match inputs or outputs of an application
- Each wire is shielded, providing a vivid, noise-free image
- Fully molded connectors for strain relief

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120025665	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

Dimensions

Cable Length	0.5 ft
--------------	--------

Technical Information

Wire Gauge	28 AWG	Cable Type	Adapter, Video
Jacket Rating	Standard / Non-Rated	Adapter Rear	BNC RGBHV Female
Adapter Front	VGA Male		