



Use this cable to connect scanners, zip drives, external storage devices and other SCSI-1/2 peripherals. It features the Micro-Density 50-pin connector found on Fast SCSI-2 host adapters, and the DB25 connector found on many peripherals. With this cable, you can connect one peripheral directly to another, or to a SCSI host adapter card.

Designed with a foil and braided shield overwrapping a twisted-pair construction, this cable uses a high quality 132 Ohm impedance wire appropriate for the SCSI-2 bus speeds.

Cable shielding provides data integrity and maximum immunity to EMI/RFI interference. The shielding is meticulously handled by 360° soldering from the wire shielding to the metal shell which shields the connector.

The squeeze latches which fasten the cable to the device are located for easy plug-in and removal, and ensure an on-going, dependable connection. Molded connectors provide strain relief and add additional protection against EMI/RFI interference.

Specifications

General Info

| | | | |
|--------------|-------|-------|-------|
| Product Line | C2G | Color | Beige |
| Type | Cable | | |

Dimensions

| | |
|--------------|-------|
| Cable Length | 10 ft |
|--------------|-------|

Technical Information

| | | | |
|--------------|-----------|---------------|-----------|
| Adapter Rear | DB25 Male | Adapter Front | MD68 Male |
|--------------|-----------|---------------|-----------|