



**C2G**  
**Discontinued - 29.5ft (9m) LC-ST 62.5/125 OM1 Duplex Multimode PVC Fiber Optic Cable (USA-Made) - Orange**  
Part No. CG-13538



With LC to ST termination, this high quality fiber optic patch cable is specifically designed for ethernet, multimedia, or communication applications. Connect fiber optic equipment to fiber optic crossconnects, interconnects, and information outlets. The small LC connector takes HALF the size of traditional SC and ST fiber connectors, since it offers twice the port density of conventional SC and ST connectors to satisfy the need for higher port density in telecom closets, equipment rooms, and work areas.

The LC connector's RJ-style latch clip design gives each connection greater durability in resisting snagging, pulls, strains and impacts during cabling installs and maintenance. Plus, it is easy to engage and disengage with the "telephone jack style" release mechanism. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 62.5/125 multimode fiber, immune to electrical interference.

Please Note: The ST connector features a bayonet locking system, while the LC connector includes an LC clip.

**Features & Benefits**

Designed to support gigabit ethernet, fibre channel, Infiniband, ATM, or any application that requires high speed data transfer	Patented injection molding process for greater durability
Optically inspected and tested for insertion loss	Pull-proof jacket design, immune to electrical interference

**Specifications**

**General Info**

Product Line	C2G	Color	Orange
UPC Number	757120135388	Country Of Origin	United States
Application Sector	Commercial, Industrial	Warranty Type	Lifetime
Type	Cable		

**Dimensions**

Cable Length	29.5 ft
--------------	---------

**Technical Information**

Fiber Optic Cable Type	Multimode, OM1	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Riser Rated	Bend Radius	50 mm
Simplex/Duplex	Duplex	Cable Type	Fiber Optic
Jacket Rating	FT4 Rated, OFNR Rated	Cable Diameter	1.8 mm
Data Transfer Rate	1 Gbps	Adapter Rear	ST Male
Adapter Front	LC Male	Fiber Size	62.5/125