



The TruLink® VGA + Stereo Audio + Serial RS232 over Cat5 allows VGA video, Stereo Audio and Serial RS232 signals to be extended over two Cat5/Cat5e/Cat6 unshielded twisted pair cables up to 300ft or 500ft at a 1920x1200 resolution*. This solution is compatible with any operating system and is truly plug and play with no drivers or software required. The transmitter and receiver are available in either a wall plate or box form factor and are interoperable allowing this solution to meet the needs of the installation environment. In addition, this solution utilizes TruChoice™ power providing the flexibility to power at either the transmitter or receiver end. TruPair™ technology allows the Extended Display Identification Data (EDID) signals, i.e. communication of the display's capabilities, to be communicated, ensuring that the content from the source is sent at the optimal resolution for the display. Built-in power surge protection and high ground loop immunity ensure high performance signal extension. The DB9 Serial RS232 port supports full-duplex data communication at 230Kbps and is fully compatible with all RS232 protocols. Point-to-point or multi-drop data communication is supported.

*Longer distances can be achieved at lower resolutions.

Features & Benefits

Extend VGA, Stereo Audio and Serial RS232 up to 300ft or 500ft at a 1920x1200 resolution

Utilizes two category cables for extension

TruPair technology ensures compatibility with any monitor

TruChoice Power allows for power at transmitter or receiver end

Specifications

General Info

Product Line	C2G	Color	White
Features	RS232	Application Sector	Commercial
Type	Transmitter		

Technical Information

Video Resolution	WUXGA (1920x1200)	Cable Diameter	4.75 mm
Connector 2	RJ-45 Female	Connector 1	3.5mm Stereo Female, DB9 Female, VGA Female