



The TruLink® VGA + Stereo Audio over Cat5 allows VGA video and Stereo Audio signals to be extended over two Cat5/Cat5e/Cat6 unshielded twisted pair cables up to 300ft at up to a 1920x1200 video resolution. The transmitter and receiver are available in either a wall plate or box form factor and are interoperable allowing this solution to meet the needs of the installation environment. In addition, this solution utilizes TruChoice™ power providing the flexibility to power at either the transmitter or receiver end. TruPair™ technology allows the Extended Display Identification Data (EDID) signals, i.e. communication of the display's capabilities, to be communicated, ensuring that the content from the source is sent at the optimal resolution for the display. Built-in power surge protection and high ground loop immunity ensure high performance signal extension.

View compatible transmitters, additional receivers and kit options on the

## Features & Benefits

Extend VGA and Stereo Audio up to 300ft at a 1920x1200 resolution

Utilizes two category cables for extension

TruPair technology ensures compatibility with any monitor

TruChoice Power allows for power at transmitter or receiver end

## Specifications

### General Info

Product Line	C2G	Color	White
--------------	-----	-------	-------

Type	Receiver
------	----------

### Technical Information

Video Resolution	WUXGA (1920x1200)	Cable Diameter	4.75 mm
------------------	-------------------	----------------	---------

Adapter Rear	3.5mm Stereo Female, VGA Female	Adapter Front	RJ-45 Female, RJ-45 Female
--------------	---------------------------------	---------------	----------------------------