

C2G Discontinued - TruLink® VGA + Stereo Audio over Cat5 Extender Double Gang Wall Plate Receiver with 4 Keystones- Aluminum Part No. CG-29279



The TruLink® VGA + Stereo Audio over Cat5 allows VGA video and Stereo Audio signals to be extended over two Cat5/Cat5e/Cat6 unshielded twisted pair cables up to 300ft at up to a 1920x1200 video resolution. The transmitter and receiver are available in either a wall plate or box form factor and are interoperable allowing this solution to meet the needs of the installation environment. In addition, this solution utilizes TruChoice™ power providing the flexibility to power at either the transmitter or receiver end. TruPair™ technology allows the Extended Display Identification Data (EDID) signals, i.e. communication of the display's capabilities, to be communicated, ensuring that the content from the source is sent at the optimal resolution for the display. Built-in power surge protection and high ground loop immunity ensure high performance signal extension. The keystones allow this plate to be integrated with Ethernet or Telephony infrastructure and will work with Leviton®, L-com®, NetKey®, ADC Krone, Hellermann Tyton, and Allen Tel inserts.

View compatible transmitters, additional receivers and kit options on the

Specifications

General Info			
Product Line	C2G	Color	Aluminum
Туре	Receiver		
Technical Information			
Video Resolution	WUXGA (1920x1200)	Cable Diameter	4.75 mm
Adapter Rear	3.5mm Stereo Female, VGA Female	Adapter Front	RJ-45 Female, RJ-45 Female