

C2G
Discontinued - TruLink® VGA + Stereo Audio + Composite Video + Audio over Cat5 Extender Double Gang Wall Plate Receiver with 4 Keystones - Wh Part No. CG-29282



The TruLink® VGA + Stereo Audio + Composite Video + Audio over Cat5 allows VGA video, Stereo Audio, Composite Video and Audio signals to be extended over tw Cat5/Cat5e/Cat6 unshielded twisted pair cables up to 300ft. VGA video is supported at up to a 1920x1200 video resolution, while Composite Video is supported at a 480i video resolution. The 3.5mm port supports Stereo Audio, while the two RCA Audio inputs accept a Stereo Audio input, mix the two channels of audio into a single signal which is sent to the receiver then duplicated so that both channels of audio are sent to the white and to the red RCA output ports at the receiver. This solution is compatible with any operating system and is truly plug and play with no drivers or software required. The transmitter and receiver are available in eith a wall plate or box form factor and are interoperable allowing this solution to meet the needs of the installation environment. In addition, this solution utilizes TruChoice™ power providing the flexibility to power at either the transmitter or receiver end. TruPair™ technology allows the Extended Display Identification Data (EDID) signals, i.e. communication of the display's capabilities, to be communicated, ensuring that the content from the source is sent at the optimal resolution fc the display. Built-in power surge protection and high ground loop immunity ensure high performance signal extension. The keystones allow this plate to be $integrated \ with \ Ethernet \ or \ Telephony \ infrastructure \ and \ will \ work \ with \ Leviton@, \ L-com@, \ Net \ Key@, \ ADC \ Krone, \ Hellermann \ Tyton, \ and \ Allen \ Tellermann \ Tyton, \ and \ Allen \ Tellermann \ Tellermannn \ Tellermannnnn \ Tellermannnnnnnnnnnnnnnnn$

View compatible transmitters, additional receivers and kit options on the $\,$

Specifications

General Info			
Product Line	C2G	Color	White
Application Sector	Commercial	Туре	Receiver
Technical Information			
Video Resolution	WUXGA (1920x1200)	Cable Diameter	4.75 mm
Connector 2	3.5mm Stereo Female, RCA Composite Video Female, RCA Female, VGA Female	Connector 1	RJ-45 Female