



C2G

Discontinued - HDMI® and VGA + Stereo Audio HDBaseT over Cat Extender Transmitter to Scaler/De-Embedder Kit

Part No. CG-29319



The HDMI and VGA + Stereo Audio HDBaseT over Cat Extender Transmitter to Scaler / De-embedder kit is an ideal solution for extending audio/video signals from a Blu-ray™ player, laptop, Cable box, or other source device to a projector, HDTV, or Monitor. This kit extends HDMI, VGA and Stereo Audio signals over a single Cat5e, Cat6, or Cat6a network patch cable up to 230 feet at a 1080p resolution for HDMI and VGA, or 115 feet at 4k for HDMI. The local HDMI output allows an additional HDMI display to be supported via an HDMI cable. Switching between HDMI and VGA inputs is made easy with three options. The automatic switching option displays the last connected device. There are also two manual switching options. The first manual switching option is the buttons on the front of the transmitter. The second manual switching option is through Serial RS232 switching which accepts serial commands from a control device, like our TruLink® A/V Controller.. The built-in scaler up-scales VGA video to a 1080p resolution, ensuring that a high performance image is displayed . The de-embedder splits the audio from HDMI video and converts it to a Stereo Audio output to support an audio system that is separate from the display. This solution is compatible with any operating system and is truly plug and play with no drivers or software required. This solution utilizes TruChoice™ power, which allows power to be supplied over the Cat cable to both the transmitter and receiver from a single power adapter placed at either the transmitter or the receiver end of the solution. HDBaseT technology supports HDCP and allows the Extended Display Identification Data (EDID) signals, i.e. communication of the display's capabilities, to pass through the extension solution ensuring that the content from the source is sent at the optimal resolution for the display. This transmitter is compatible with any of the HDMI HDBaseT receivers offered by C2G and works with our DB9 to RJ25 Serial RS232 cables.

Note: Stranded Cat5e/6/6a patch cables may be used for HDMI extension applications up to 230ft. Shielded, solid conductor Cat6 or HDBaseT Certified Cat6a network cabling is recommended for applications where the category cable must be coiled, is run near other high-frequency signaling cables, or in high EMI/RFI environments. For best performance use a Cat6 Solid Shielded Patch Cable or anHDBaseT Certified Cat6a Patch Cable.

Features & Benefits

Three methods for input switching: Auto, Manual, and Serial RS232

Extend HDMI up to 115ft at 4k and up to 230ft at 1080p

Utilizes a single Cat5e, Cat6 or Cat6a cable for extension

De-embeds audio from an HDMI A/V signal

HDBaseT technology supports EDID pass through

Extend VGA up to 230ft at 1080p

Scales VGA video to a 1080p resolution

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120293194	Country Of Origin	Taiwan, Province Of China
Application Sector	Commercial	Warranty Type	5-Year
Type	Active Device, Extender, HDBaseT, Kit		

Listing Agencies / 3rd Party Agencies

CE Certified	Yes	FCC Compliant	Yes
--------------	-----	---------------	-----

Buy American Act Compliance

TAA Compliant	Yes
---------------	-----

Technical Information

Video Resolution	1080p, 4K, 4K 30Hz	Adapter Rear	HDMI Female, RJ-45 Female, RJ-11 Female, 3.5mm Stereo Female
------------------	--------------------	--------------	--