

Discontinued - TruLink® VGA + Stereo Audio + Serial RS232 over Cat5 Extender Box Transmitter to Aluminum Wall Plate Receiver Kit - 500ft Part No. CG-29411





The TruLink® VGA + Stereo Audio + Serial RS232 over Cat5 kit is a complete solution for extending VGA video, Stereo Audio and Serial RS232 signals over two Cat5/Cat5e/Cat6 unshielded twisted pair cables up to 500ft at a 1920x1200 resolution*. This solution is compatible with any operating system and is truly plug and play with no drivers or software required. The transmitter and receiver are available in either a wall plate or box form factor and $are interoperable allowing this solution to meet the needs of the installation environment. In addition, this solution utilizes TruChoice \verb|^TM| power than the property of the installation in the property of the installation of the installation and the property of the installation of$ providing the flexibility to power at either the transmitter or receiver end. TruPair™ technology allows the Extended Display Identification Data [EDID] signals, i.e. communication of the display's capabilities, to be communicated, ensuring that the content from the source is sent at the optimal resolution for the display. Built-in power surge protection and high ground loop immunity ensure high performance signal extension. The DB9 Serial RS232 port supports full-duplex data communication at 230Kbps and is fully compatible with all RS232 protocols. Point-to-point or multi-drop data communication is supported.

*Longer distances can be achieved at lower resolutions.

Features & Benefits

Extend VGA, Stereo Audio and Serial RS232 up to 500ft at a 1920x1200 resolution		Utilizes two category	Utilizes two category cables for extension	
TruPair technology ensures compatibility with any monitor		TruChoice Power all	TruChoice Power allows for power at transmitter or receiver end	
Specifications				
General Info				
Product Line	C2G	Color	Aluminum	
Features	RS232	Туре	Receiver, Transmitter	
Technical Information				
Video Resolution	WUXGA (1920x1200)	Cable Diameter	4.75 mm	