



The HDMI over Coax Extender is the perfect solution for extending high definition HDMI audio and video signals up to 160 feet to support a point to point connection or to distribute those signals to up to sixteen displays for support of a small scale digital signage system. This solution utilizes a single RG6 coax cable to connect from transmitter to receiver and additional receivers may be cascaded to support additional displays. The system will auto adjust feedback, equalization and amplification allowing this solution to be customized to support any length.

Connect a Blu-ray player, laptop computer, gaming system or streaming media player, directly to the input of the transmitter with a HDMI cable. Use a single, industry standard, RG6 coax cable to connect an output of the transmitter to the input of a receiver. Each receiver features an RG6 output which may be used to support an additional receiver. Finally, connect a HDMI cable from the HDMI output of the receiver to an HDMI input on a HDTV, projector or monitor to supply high definition audio and video.

Features & Benefits

| | |
|--|--|
| Extend HDMI audio/video signals up to 160 feet | Distribute signals to up to sixteen displays |
| Supports 3D Video at up to a 1080p resolution | IR control and EDID signal support |

Specifications

General Info

| | | | |
|--------------------|-------------------------|-------------------|------------------------------|
| Product Line | C2G | Color | Black |
| UPC Number | 757120294542 | Country Of Origin | China |
| Application Sector | Commercial, Residential | Type | Active Device, Extender, Kit |

Listing Agencies / 3rd Party Agencies

| | | | |
|--------------|-----|---------------|-----|
| CE Certified | Yes | FCC Compliant | Yes |
|--------------|-----|---------------|-----|

Technical Information

| | | | |
|-----------------------|-----------|----------------------|----------|
| Video Resolution | 1080p | Bend Radius | 50 mm |
| Data Transfer Rate | 10.2 Gbps | Video Output Support | HDMI |
| Operating Temperature | 5°-35°C | Operating Humidity | 5-90% RH |

Video Input Support

HDMI

Storage Temperature

5° - 35° C
