



Audio/video installations in educational and commercial settings often require in-wall rated cable. Our CMG-rated line was specifically engineered to meet this requirement while overcoming common challenges faced by installers in these environments. Low-Profile connectors (1.41in total depth) save valuable space in the gang box.

- This cable is constructed from three 75 Ohm coaxial cables using 26 AWG center conductors and features a tinned copper braid that provides 92% coverage over a foil shield. This design protects the cable from any EMI/RFI interference and ensures that the highest quality signal is transferred for optimal audio/video performance.

CMG-rated cables meet many NEC requirements for Communications Cables General Purpose In Wall Use. Our cables meet the following ratings: CMG, FT4, CM, CL3, CL2, CMX, CL3X, and CL2X.

Always check with your local authority on building requirements to verify cable requirements before beginning any installation.

Specifications

General Info

Product Line	C2G	UPC Number	757120401186
Country Of Origin	China	Warranty Type	Lifetime
Type	Cable		

Dimensions

Cable Length	50 ft
--------------	-------

Technical Information

Jacket Application	In-Wall Rated	Cable Type	Audio
Jacket Rating	CMG Rated, FT4 Rated	Adapter Rear	RCA Composite Video Male, RCA Stereo Audio Male
Adapter Front	RCA Composite Video Male, RCA Stereo Audio Male		