



C2G
Discontinued - 75ft (22.8m) VGA Monitor/Projector Cable M/M - Plenum CMP-Rated
Part No. CG-40258

Thin (only 0.28 inches in diameter) and very flexible for easier installation! Use this extension cable in any educational or commercial installation for video projectors, plasma screens, LCD or CRT monitors, or installations where the cable must perform over long distances. Cable construction consists of three 75 Ohm 28 AWG coax cables plus three 26 AWG twisted pairs and two 26 AWG conductors ensuring signal integrity in your installation.

The coax cables feature a tinned copper braid providing 93% shield. Besides the metal HD15 connector housing, the cable is shielded by a tinned copper braid providing a minimum of 85% coverage, and by aluminum foil and drain wire to provide 100% coverage.

The low-smoke CMP-rated PVC outer jacket and FEP inner insulator provide the fire protection required to run these cables within walls and air plenums without the need for conduit. Don't be misled by cable dealers selling low cost, so-called plenum cables that Don't meet the minimum requirements for plenum rating, those cables will cost you much more in the end. Instead, trust our plenum-rated high resolution cable for your installation!

Please Note: UXGA provides a screen resolution of 1600 x 1200 pixels.

Please Note: Pin 9 is not loaded. Pin 9 is not required for standard computer video applications.

Features & Benefits

| | |
|---|---|
| Designed to perform over long distances | Plenum CMP rated for cable runs through walls and drop ceilings with plenum air space |
| Shielded to prevent unwanted noise and interference | Connector thumbscrews for a quick and easy connection |

Specifications

General Info

| | | | |
|---------------|----------|--------------------|-------------------------|
| Product Line | C2G | Application Sector | Commercial, Residential |
| Warranty Type | Lifetime | Type | Cable |

Dimensions

| | |
|--------------|-------|
| Cable Length | 75 ft |
|--------------|-------|

Technical Information

| | | | |
|--------------------|----------------------|--------------|----------|
| Jacket Application | Plenum Rated | Cable Type | Video |
| Jacket Rating | CMP Rated, FT6 Rated | Adapter Rear | VGA Male |
| Adapter Front | VGA Male | | |
