

C2G

Discontinued - 125ft (38.1m) VGA Monitor/Projector Cable M/M - Plenum CMP-Rated

Part No. CG-40260

Thin (only 0.28 inches in diameter) and very flexible for easier installation! Use this extension cable in any educational or commercial installation for video projectors, plasma screens, LCD or CRT monitors, or installations where the cable must perform over long distances. Cable construction consists of three 75 0hm 28 AWG coax cables plus three 26 AWG twisted pairs and two 26 AWG conductors ensuring signal integrity in your installation.

The coax cables feature a tinned copper braid providing 93% shield. Besides the metal HD15 connector housing, the cable is shielded by a tinned copper braid providing a minimum of 85% coverage, and by aluminum foil and drain wire to provide 100% coverage.

The low-smoke CMP-rated PVC outer jacket and FEP inner insulator provide the fire protection required to run these cables within walls and air plenums without the need for conduit. Don't be misled by cable dealers selling low cost, so-called plenum cables that Don't meet the minimum requirements for plenum rating, those cables will cost you much more in the end. Instead, trust our plenum-rated high resolution cable for your installation!

Please Note: UXGA provides a screen resolution of 1600 x 1200 pixels.

Please Note: Pin 9 is not loaded. Pin 9 is not required for standard computer video applications.

Plenum Rated

Features & Benefits

Designed to perform over long distances		Plenum CMP rated for cable runs through walls and drop ceilings with plenum air space		
Shielded to prevent unwanted noise and interference		Connector thumbscrews for a quick and easy connection		
Specifications				
General Info				
Product Line	C2G	Application Sector	Commercial, Residential	
Warranty Type	Lifetime	Туре	Cable	
Dimensions				
Cable Length	125 ft			
Technical Information				

Jacket Application

UXGA [1600x1200]

Video Resolution

Cable Type	Video	Jacket Rating	CMP Rated, FT6 Rated
Connector 2	VGA Male	Connector 1	VGA Male
Video Output Support	VGA	Video Input Support	VGA