

## C2G Discontinued - 25ft (7.6m) Serial RS232 DB9 Null Modem Cable with Low Profile Connectors M/M - In-Wall CMG-Rated



Audio/Video installations in educational and commercial settings often require in-wall rated cable. Our CMG-rated line was specifically engineered to meet this requirement while overcoming common challenges faced by installers in these environments. Low-Profile connectors (1.25 in total depth) save valuable space in the gang box, while the rounded shape accommodates smaller monitor mounts so that the cable can be easily hidden from view.

Specifically designed to support RS-232/Serial communications, this cable is fully shielded to prevent unwanted EMI/RFI interference. The fully molded cable design delivers excellent strain relief, while connector thumbscrews provide a quick and easy connection every time.

The transmit and receive signals are crossed to ensure proper data transmission.

 ${\it CMG-rated \ cables \ meet \ with \ many \ NEC \ requirements \ for \ Communications \ Cables \ - \ General \ Purpose \ In \ Wall \ Use \ . \ Our \ cables \ meet \ the \ following \ ratings: \ CMG, \ FT4 \ [Canada]}$ 

## Features & Benefits

reatures & Denemits	2			
Designed to support RS-232/Serial communications Shielded to prevent unwanted EMI/RFI interference		CMG-rated for in-wall use	CMG-rated for in-wall use  Connector thumbscrews for a quick and easy connection	
		Connector thumbscrews f		
Specifications				
General Info				
Product Line	C2G	Color	Black	
UPC Number	757120521709	Country Of Origin	Vietnam	
Features	RS232	Application Sector	Commercial, Industrial, Residential	
Warranty Type	Lifetime	Туре	Cable	
Dimensions				
Product Length US	25.0 FT	Cable Length	25 ft	
Technical Information				
Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	28 AWG	
Jacket Application	In-Wall Rated	Cable Type	Modem, Serial	
Jacket Rating	CMG Rated, FT4 Rated	Adapter Rear	DB9 Male	
Adapter Front	DB9 Male			