



RapidRun® is designed to be the standard for in-wall audio/video installations. Using pre-terminated Break-away flying leads and wall plates with an in-wall runner ensures flexible, efficient, high quality connections for all types of equipment, with no field terminations.

Ideal for educational and institutional installations, this flying lead is commonly used on the display (projector) end of classroom setups with the corresponding wall plate used at the teacher's station.

Please note: Each complete RapidRun Multi-Format solution requires a break-away flying lead or wall plate to terminate each end of the runner cable. Each runner requires (2) break-away flying leads, (2) wall plates, OR (1) break-away flying lead and (1) wall plate.

<

## Features & Benefits

Designed for use with RapidRun Multi-Format runner cables

Compatible with RapidRun Multi-Format VGA, 3.5mm wall plates and flying leads

Fits in a standard single gang wall box

## Specifications

### General Info

Product Line	C2G	Color	Aluminum
UPC Number	757120600367	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Keystone, Wall Plate Insert		

### Technical Information

Wire Gauge	24 AWG	Video Resolution	UXGA (1600x1200)
Number of Gangs	1	Adapter Rear	RapidRun 15-pin Male
Adapter Front	VGA Female, 3.5mm Stereo Female		