

C2G Superbooster USB Extenders deliver reliable USB signal transmission for USB devices, allowing devices such as cameras, interactive whiteboards and printers to be placed at greater distances from the host computer.



The C2G Superbooster USB Camera Extender has undergone rigorous compatibility testing with industry-leading video conferencing cameras, ensuring total reliability and deployment confidence, plus saving valuable time for AV integrators as well.

This camera extender is designed with chipset technology that offers a higher compatibility rate than other USB extenders on the market. The C2G Superbooster USB Camera Extender has been tested and proven by C2G to support leading PTZ cameras.

This Superbooster® USB Camera Extender provides reliable USB data extension from a computer to a USB camera up to 150 feet (45.7m) over a standard Cat6 network cable – making it an ideal solution for conference rooms, command centers, classrooms, auditoriums and medical facilities.

This plug-and-play solution consists of one wall plate transmitter and one wall plate receiver.

## Features & Benefits

Tested and proven to support leading PTZ cameras at 1080p or 4K resolutions depending on the camera	Extends a USB camera up to 150ft (45.7m) over Cat6		
Lower power consumption - typically 0.5W	Bi-directional data and power transfer – simplifies installation by allowing the same module to be used as either a transmitter or receiver		
As easy to use as a passive cable. Plug and play with no software or drivers required	Up to 1.5A power delivery from host to device		
Optional external power to support high-current devices(up Compatible with USB 2.0. Compatible to USB 1.1 if a USB 2.0 hub is used on the device end			

Backed by a 5-year warranty

## Specifications

## General Info

Product Line	C2G	Color	White
UPC Number	757120542759	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	5-Year
Туре	Active Device, Extender, Kit		
Dimensions			
Product Width US	1.73 in	Product Depth US	1.2 in
Product Height US	4.19 in	Product Length US	1.73 in

Listing Agencies / 3rd Party Agencies						
CE Certified	Yes	FCC Compliant	Yes			
REACH Compliant	Yes					
Additional Information						
RoHS Conformant	Yes					
Technical Information						
Number of Gangs	1	Amperage	1.5 A			
Data Transfer Rate	480 Mbps	Adapter Rear	RJ-45 Female, USB-C Female			
Adapter Front	USB-C Female, RJ45 Female					