



This OM3 Duplex Multimode Fiber Optic Cable is ideal for connecting 10GBase-SR, 10GBase-LRM, SFP+ and QSFP+ transceivers for 10 gigabit network connections. The Uniboot connector allows two fibers to be carried through a single jacket. This reduces the surface area of the cable when compared to standard duplex cables, allowing this cable to facilitate improved airflow within a data center. This cable provides backward compatibility with existing 50/125 equipment and the performance headroom required to support LED and VCSEL laser light sources, and 10 gigabit Ethernet applications in a datacenter or wiring closet.

<

## Features & Benefits

- Uniboot connector allows two fibers to be carried within a single jacket
- Constructed to support OM3 transmission standards
- Support for 10 Gigabit Ethernet communication

## Specifications

### General Info

Product Line	C2G	Color	Aqua
UPC Number	757120010135	Country Of Origin	China
Application Sector	Commercial, Industrial	Warranty Type	Lifetime
Type	Cable		

### Dimensions

Product Length US	6.6 FT	Cable Length	6.6 ft
-------------------	--------	--------------	--------

### Technical Information

Fiber Optic Cable Type	Multimode, OM3	Jacket Material	PVC (Polyvinyl Chloride)
Jacket Application	Riser Rated	Bend Radius	10 mm
Simplex/Duplex	Duplex	Cable Type	Fiber Optic
Jacket Rating	FT4 Rated, OFNR Rated	Cable Diameter	2 mm

---

Data Transfer Rate	10 Gbps	Adapter Rear	LC Male, LC Male
--------------------	---------	--------------	------------------

---

Adapter Front	LC Male, LC Male	Fiber Size	50/125
---------------	------------------	------------	--------

---