



This precision-engineered cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). The DVI-I dual link configuration provides enough bandwidth for resolutions up to 2048 x 1536 pixels and allows high speed transmission up to 9.9 Gbps. Three analog 30 AWG coaxial lines enable high speed analog transmission.

Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: white.

Please Note: The DVI-I plug connector can only be inserted into a DVI-I interface.

Features & Benefits

Connects to an existing DVI-I male cable for extra distance

Supports resolutions up to 2048x1536 at 9.9Gbps

Available in lengths up to 3m

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120293217	Country Of Origin	China
Application Sector	Commercial, Residential	Warranty Type	Lifetime
Type	Cable		

Dimensions

Cable Length	6.6 ft
--------------	--------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
-----------------	--------------------------	------------	--------

Video Resolution	QXGA (2048x1536)	Cable Type	Extension, Video
Jacket Rating	Standard / Non-Rated	Data Transfer Rate	9.9 Gbps
Adapter Rear	DVI-I Dual Link Female	Adapter Front	DVI-I Dual Link Male
