



Cost-effective solution that provides high bandwidth and transmission rates over longer distances. With LC to LC termination, this high quality fiber optic patch cable is specifically designed for gigabit ethernet applications. The patented injection molding process provides each connection greater durability in resisting pulls, strains and impacts from cabling installs.

Each cable is 100% optically inspected and tested for insertion loss before you receive it. A pull-proof jacket design surrounds the popular 9/125 Single-mode fiber, immune to electrical interference.

## Features & Benefits

Designed to support gigabit ethernet applications

Patented injection molding process for greater durability

Optically inspected and tested for insertion loss

Pull-proof jacket design, immune to electrical interference

## Specifications

### General Info

|                    |                        |                   |          |
|--------------------|------------------------|-------------------|----------|
| Product Line       | C2G                    | Color             | Yellow   |
| UPC Number         | 757120371052           | Country Of Origin | China    |
| Application Sector | Commercial, Industrial | Warranty Type     | Lifetime |
| Type               | Cable                  |                   |          |

### Dimensions

|                   |        |              |        |
|-------------------|--------|--------------|--------|
| Product Length US | 9.8 FT | Cable Length | 9.8 ft |
|-------------------|--------|--------------|--------|

### Technical Information

|                        |                       |                 |                          |
|------------------------|-----------------------|-----------------|--------------------------|
| Fiber Optic Cable Type | OS2, Single-Mode      | Jacket Material | PVC (Polyvinyl Chloride) |
| Jacket Application     | Riser Rated           | Bend Radius     | 50 mm                    |
| Simplex/Duplex         | Simplex               | Cable Type      | Fiber Optic              |
| Jacket Rating          | FT4 Rated, OFNR Rated | Cable Diameter  | 1.8 mm                   |

---

Adapter Rear

LC Male

Adapter Front

LC Male

---

Fiber Size

9/125

---