

The Patented (US 11,444,419 B2) Retractable Universal Mount 4K HDMI Adapter Ring is the perfect addition to conference rooms, huddle spaces, lecture halls, or classrooms to make sure that anyone can connect. The standard configuration includes the adapters to connect nearly any device to the in-room display while supporting up to a 4K video resolution. Choose from HDMI to DisplayPort, Mini DisplayPort, USB-C, Lightning, or VGA to meet connectivity challenges.

**Color Coded Adapters**

The DisplayPort, Mini DisplayPort, USB-C, and VGA adapters are color-coded with a band that saves time and frustration by making it easy to identify the adapter you need.

**Integrated Pull Tab**

Quickly grab the adapters when you need them with the integrated Pull Tab that is also available to be customized to feature your company or organization logo. Minimum order quantities apply to customized Pull Tabs.

**Retractable Universal Mount**

The Retractable Universal Mount attaches to any flat surface, like a table or lectern, providing mounting flexibility to fit your environment best. The retractor extends out to 4.9ft, ensuring that the adapters are always within reach when needed, and the retractor tested to over 20,000 extension cycles for long service life.

**Tools Included**

To simplify the process, the installation tool is included.

**Additional Technical Spec**

**Signal Specifications**

- USB Type-C to HDMI Adapter: 100% Functional Test at 4K/60Hz/4:4:4 Resolution with Standard AV Test Equipment
- DisplayPort to HDMI Adapter: 100% Functional Test at 4K/30Hz Resolution with Standard AV Test Equipment
- Mini DisplayPort to HDMI Adapter: 100% Functional Test at 4K/30Hz Resolution with Standard AV Test Equipment
- Lightning to HDMI Adapter: 100% Functional Test at 1080p Resolution with Standard AV Test Equipment
- VGA to HDMI Adapter: 100% Functional Test at 1080p/60Hz Resolution with Standard AV Test Equipment

**Electrical Specifications**

- USB Type-C to HDMI Adapter Power Consumption: 1050mW (210mA/5.0V)
- DisplayPort to HDMI Adapter Power Consumption: 396mW (120mA/3.3V)
- Mini DisplayPort to HDMI Adapter Power Consumption: 396mW (120mA/3.3V)

**Physical Specifications**

- Operating Temperature: 0°C - 40°C (0% - 90%RH)
- Storage Temperature: -10°C - 60°C (0% - 90%RH)

**Physical Characteristics**

- All Connectors (Except Lightning): Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black, Shell: Nickel Plated
- Adapter Hood: Molded Black PVC
- USB Type-C to HDMI Adapter Color Band: 12x1.5mm
- DisplayPort to HDMI Adapter Color Band: Red 12x1.5mm
- Mini DisplayPort to HDMI Adapter Color Band: Yellow 12x1.5mm
- VGA to HDMI Adapter Color Band: Purple 12x1.5mm
- Retractor: 63.5x63.5x17.5mm, Black Steel Wire OD: 1.2mm, Retracting Cable Length: 6ft, ABS Shell, with Hex Nut Tool and Black Locking Coupler (x2)
- Black Metal Screws (x4): 6.8x22mm, M3, Material: Steel
- Black Metal Screws (x4): 6.0x22.5mm, M3.5, Material: Steel
- PC Eyelet: 17.8x4.7x2.6mm, Black, Material: PC
- Pull Tab: 80x25x2mm, Material: Polyester, Black Background, White Text, with Black Eyelet
- Universal Mounting Bracket: 85x65x1.2mm, Material: C.R.S. Rigidity: 1/4H, Color: Black
- Product is CE marked and conforms to 2011/65/EU ROHS 2



**Features & Benefits**

Adapters support up to a 4K video resolution, so meeting attendees will be able to see the displayed content for improved comprehension and detailed decision making

The included Lightning adapter supports up to a 1080p video resolution

The DisplayPort, Mini DisplayPort, and USB-C adapters are color coded, so no more frustration trying to find the adapter that you typically use for your laptop

Integrated pull tab, so the adapters can be accessed quickly or easily reached when they are tucked away

Retractable Universal Mount attaches to any flat surface, providing flexibility when installing

Installation tools are included, so you save time and money by not needing to purchase any additional tools

Backed by a Lifetime Warranty for peace of mind

**Specifications**

**General Info**

Product Line	C2G	Color	Black
--------------	-----	-------	-------

---

UPC Number	757120298939	Country Of Origin	China
Features	Color-Coded, Retractable	Application Sector	Commercial, Residential
Warranty Type	5-Year	Type	Active Device, Adapter, Adapter Ring

---

#### Technical Information

---

Jacket Material	PVC (Polyvinyl Chloride)	Video Resolution	1080p, 1080p 60Hz, 4K, 4K 30Hz, 4K 60Hz
Cable Type	Adapter, Flexible	Adapter Rear	DisplayPort Male, Mini DisplayPort Male, VGA Male, Lightning Male, USB-C Male, USB-A Male
Adapter Front	HDMI Female, HDMI Female, HDMI Female, HDMI Female, HDMI Female	Operating Temperature	0°-40°C
Storage Temperature	-10° - 60° C		

---