



### TruLink™ Wireless USB to HDMI® Kit

#### Wirelessly transmit audio and HDMI video between a computer and a display


The TruLink USB to HDMI Kit provides a powerful solution to stream audio and video to a remote monitor, projector or television. Engineered to incorporate Ultra Wideband technology, this kit allows for in-room wireless connectivity up to 30 feet (line of sight) between the computer and display. Setup is simple and usage is seamless because all required video drivers are embedded in the host adapter\*, ensuring a quick, plug and play experience. Our new Quick Link feature allows additional users with host adapters to quickly connect to the device adapter with no additional steps required to “pair” the devices. This highly secure wireless connection is ideal for classrooms and conference rooms, or to display audio/video content from your laptop to your home entertainment system. Two flexible device adapter mounting options are included, a desk mount and a wall mount.

#### Features:

- Supports up to UXGA (1600x1200 pixels) and WSXGA (1680x1050 pixels) video resolutions with audio
- Video streaming up to 720p (720p only available at resolution 1024x768 pixels or lower)
- CD-less auto-install driver installation for PC (for Windows® only)
- Mac® OS compatible (10.4 and higher. Video driver included on the CD)
- New Quick Link feature allows additional host adapters to connect to an existing device adapter with no pairing necessary
- WiMedia Data Rates: 53 to 480Mbps
- Ultra Wideband operates in the frequency of 6.3GHz to 7.9GHz (WiMedia™ Band Group 3)
- Warranty: 1 year

Item#	Description
29354	TruLink Wireless USB to HDMI Kit

Note: Mac drivers are not embedded in the host adapter



# TruLink® Wireless USB to HDMI® Kit

## General Specifications:

Data Rates (Mbps):	53.3, 80, 106.7, 160, 200, 320, 400, 480
Maximum Resolution:	UXGA - 1600 x 1200, WSXGA - 1680 x 1050 720p (1024 x 768, 1280 x 720, 1280 x 800) for video playback
Operating Systems Supported:	Windows® XP, Vista (32 or 64 bit), Windows® 7 (32 or 64 bit), Mac OSX
USB Standard:	USB 2.0

## Wireless Specifications:

System Standards:	WiMedia PHY v1.1, Wireless USB 1.0
WiMedia Band Groups:	Band Groups 1, 3, 6 (3.1 - 8.967 GHz)
WiMedia Channels:	TFCs 1 through 10
Range (Line of Sight):	30ft

## Power Adapter Specifications:

Power Input:	100-240VAC ~ 50/60Hz 0.5A Max.
Power Output:	5VDC 2.5A 12.5W Max.
Pin Diameter:	3.5mm
Center Pin Polarity:	Positive

## Physical Characteristics:

Video Output Connector:	Type A HDMI Female - 19pin
LED Light Colors:	Blue - Power Green - Link
Housing Material:	Plastic
Operating Temperature Range:	0° - 50°C
Operating Humidity Range:	10 - 95%
Weight:	0.05lbs - USB Transmitter 0.35lbs - Wireless Receiver
Dimensions:	2.60 x 0.91 x 0.50in - USB Transmitter 5.60 x 3.15 x 1.25in - Wireless Receiver

