



RapidRun[®] S-Video + Composite Video + Stereo Audio Wall Plate

- Color Code: Blue (for use with the Multimedia Runners)
- RCA Connectors are color-coded yellow/red/white for Composite Video and Stereo Audio
- Fits into most J-boxes
- Compatible with Leviton Decora[®] brand cover plates.
- Lifetime Warranty

*The specifications apply only to the raw cable used to construct the cable assemblies

Note: Decora[®] is a registered trademark of Leviton Manufacturing Company, Inc. This product is not manufactured or endorsed by the Leviton Manufacturing Company, Inc

RapidRun® S-Video + Composite Video + Stereo Audio Wall Plate

Electrical Characteristics:

Impedance:	75 ± 5Ω
Capacitance:	66.2 ± 5 pF/m nom
Velocity of Propagation:	78 ± 1 %
DC Resistance:	0.221 Ω/m at 20°C
Dielectric Strength:	500VAC/ 1 minute; No breakdown
Insulation Resistance (500V):	100MΩ/KM at 20°C

Frequency	Conductor 1 - Red		Conductor 2 - Green		Conductor 3 - Blue		Conductor 4 - Black		Conductor 5 - White	
	dB/15m	dB/45m	dB/15m	dB/45m	dB/15m	dB/45m	dB/15m	dB/45m	dB/15m	dB/45m
1 MHz	0.12	0.42	0.24	0.85	0.18	0.73	0.11	0.71	0.16	0.78
10 MHz	0.86	2.53	0.9	2.89	0.89	2.84	0.75	2.76	0.85	2.94
50 MHz	2.07	6.13	2.23	6.55	20.9	6.44	2.04	6.42	2.11	6.65
100 MHz	2.98	9.06	3.23	9.49	3.06	9.28	3.01	9.37	3.12	9.63
200 MHz	4.45	13.58	4.87	14.21	4.53	13.79	4.57	14.17	4.55	14.33
400 MHz	6.72	20.56	7.75	21.83	6.93	20.98	7.16	20.93	6.96	21.67
700 MHz	9.95	29.84	12.01	31.24	10.24	30.27	10.81	28.08	10.25	31.55
1000 MHz	13.20	42.75	17.52	41.68	14.01	42.53	15.49	40.54	14.49	40.87

Physical Characteristics:

Voltage Rating:	30V
Temperature Rating:	80°C
Operating Temperature Range:	-25° C - 80°C
Minimum Bend Radius:	135 ± 5mm

Approvals:	RoHS Compliant
Warranty:	Lifetime
Package Type:	Box

Item	Description	Weight
40743	RapidRun S-Video + Composite Video + Stereo Audio Wall Plate – White	0.24
40899	RapidRun S-Video + Composite Video + Stereo Audio Wall Plate – Ivory	0.24
42031	RapidRun S-Video + Composite Video + Stereo Audio Wall Plate – Black	0.24

Specifications: S-Video + Composite Video + Stereo Audio Wall Plate

Conductor (Qty. 5):

Conductor Type:	28AWG 7/36 Tinned Copper
Insulation:	Minimum Avg. Thickness: 0.7mm Foam FEP
Shield:	AL-Foil – 100% Coverage Braided Tinned Copper 42±3/0.12 85% Min. Coverage
Jacket:	Minimum Avg. Thickness: 0.7 mm PVC: (1) red, (1) green, (1) blue, (1) black, (1) white

RCA Connector (Qty. 3):

Connector Type:	RCA
Gender:	Female
Contact Material:	Brass, 3µm Gold Plating
Insulation:	Yellow PBT, Red PBT, White PBT

S-Video Connector (Qty. 1):

Connector Type:	4-pin Mini Din
Gender:	Female
Contact Material:	Brass, 3µm Gold Plating
Insulation:	Black PBT

RapidRun Connector (Qty. 2):

Connector Type:	DIN 12-pin
Gender:	Male
Contact Material:	Brass, 3µm Gold Plating
Insulation:	Black PBT

Overall Cable

Jacket:	Blue heat shrink
---------	------------------

