

FCC Statement

Note: This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

FCC Statement - §15.105(b):

"This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution - §15.21:

"Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment."

© 2018 Legrand All Rights Reserved
rev.07/18 QSG – 60218

C2G
A brand of  **legrand**

60 Woodlawn Street
West Hartford, CT 06110
Phone 800.293.4970
www.c2g.com

C2G[®]
A brand of  **legrand**

(US) RapidRun[®] HDMI[®] + USB Extender
(FR) RapidRun[®] HDMI[®] + Extension USB
(ES) Extensor RapidRun[®] HDMI[®] + USB

Model 60218

(US) RAPIDRUN® HDMI® + USB EXTENDER QUICK START GUIDE
(FR) RAPIDRUN® HDMI® + EXTENDER USB GUIDE DE DÉMARRAGE RAPIDE
(ES) RAPIDRUN® HDMI® + USB EXTENDER GUÍA DE INICIO RÁPIDO

PACKAGE CONTENTS

- 1 x Rapid Run HDMI+USB Extender (TX)
- 1 x Rapid Run HDMI+USB Extender (RX)
- 2 x USB-A to Micro USB-B Cables
- Quick Start Guide

DEVICE INSTALLATION

Note:

- Prior to installation ensure that all devices are powered off.

Step 1: Connect an HDMI cable (not included) from the source device to the HDMI INPUT of the transmitter (TX).

Step 2: Connect the included USB-A to Micro USB-B cable from a USB source device to the USB INPUT of the transmitter (TX).

Step 3: Connect the TX connector of the RapidRun Optical Runner Cable (not included) to the RUNNER TX port on the transmitter (TX).

Step 4: Connect the RX connector of the RapidRun Optical Runner Cable to the RUNNER RX port on the receiver (RX).

Step 5: Connect an HDMI cable (not included) from the display to the HDMI OUTPUT of the receiver (RX).

Step 6: Connect a USB cable (not included) from a interactive USB device to the USB OUTPUT (USB-A) of the receiver (RX).

Step 7: Connect the included USB-A to Micro USB-B cable to the POWER port on the receiver (RX). Then connect that USB cable to reliable USB power source and power on all devices.

C2G WARRANTY

At C2G we want you to be totally confident in your purchase. That is why we offer a warranty on this device. If you experience problems due to workmanship or material defect for the duration of this warranty, we will repair or replace this device.

To request a Return Merchandise Authorization (RMA) number, contact customer service at 800-293-4970 or www.c2g.com.

CONTENU DE L'EMBALLAGE

- 1 x Rapid Run HDMI + Extension USB (TX)
- 1 x Rapid Run HDMI + Extension USB (RX)
- 2 x USB-A à Micro USB-B Câbles
- Guide de démarrage rapide

INSTALLATION DE L'APPAREIL

Remarque :

- Avant l'installation, vérifiez que tous les appareils sont éteints.

1re étape : Connectez un câble HDMI (non fourni) de l'appareil source à l'entrée HDMI INPUT de l'émetteur (TX).

2e étape : Connectez le câble USB-A inclus au câble Micro USB-B d'un périphérique source USB à l'entrée USB INPUT de l'émetteur (TX).

3e étape : Raccordez le connecteur TX du câble de cœureur optique RapidRun (non fourni) au port RUNNER TX de l'émetteur (TX).

4e étape : Connectez le connecteur RX du câble Runner Optical Runner au port RUNNER RX sur le récepteur (RX).

5e étape : Connectez un câble HDMI (non inclus) de l'affichage à la sortie HDMI OUTPUT du récepteur (RX).

6e étape : Connectez un câble USB (non fourni) d'un périphérique USB interactif à la sortie USB OUTPUT (USB-A) du récepteur (RX).

7e étape : Connectez le câble USB-A inclus au câble Micro USB-B au port POWER du récepteur (RX). Connectez ensuite ce câble USB à une source d'alimentation USB fiable et allumez tous les appareils.

GARANTIE C2G

Chez C2G, nous voulons que vous ayez une confiance totale dans votre achat. C'est ce qui explique que nous offrons une garantie pour cet appareil. En cas de défaut de matériau ou de fabrication pendant la durée de cette garantie, nous réparerons ou nous remplacerons cet appareil.

Pour demander un numéro de RMA (Return Merchandise Authorization, Autorisation de retour de marchandise), priez de contacter le service Clientèle au n° 800-293-4970 ou sur le site www.c2g.com.

CONTENIDO DEL PAQUETE

- 1 x Local extender
- 1 x Extensor remote
- 1 x USB 3.1 Gen 1 Cable
- Guía de instalación rápida

INSTALACIÓN DEL DISPOSITIVO

Nota:

- Antes de la instalación, asegúrese de que todos los dispositivos estén apagados.

Paso 1: Conecte un cable HDMI (no incluido) desde el dispositivo fuente a la ENTRADA HDMI del transmisor (TX).

Paso 2: Conecte el cable USB-A a Micro USB-B incluido desde un dispositivo fuente USB a la ENTRADA USB del transmisor (TX).

Paso 3: Conecte el conector TX del cable de recorrido óptico RapidRun (no incluido) al puerto TX RUNNER en el transmisor (TX).

Paso 4: Conecte el conector RX del cable de recorrido óptico RapidRun al puerto RUNNER RX en el receptor (RX).

Paso 5: Connect an HDMI cable (not included) from the display to the HDMI OUTPUT of the receiver (RX).

Paso 6: Conecte un cable USB (no incluido) desde un dispositivo USB interactivo a la SALIDA USB (USB-A) del receptor (RX).

Paso 7: Conecte el cable USB-A incluido a Micro USB-B al puerto POWER del receptor (RX). Luego, conecte ese cable USB a una fuente de alimentación USB confiable y encienda todos los dispositivos.

Garantía C2G

Desde C2G queremos que tenga plena confianza en su compra. Por eso ofrecemos una garantía para este dispositivo. Si experimenta cualquier problema debido a un defecto en la fabricación o en los materiales durante el período de garantía, repararemos o reemplazaremos este dispositivo.

Para solicitar un número de autorización de devolución de mercancía (RMA), póngase en contacto con el servicio de atención al cliente en el 800-293-4970 o en www.c2g.com.