

# WALL MOUNT RACKS AND BRACKETS

STANDARD EIA WALL MOUNT RACKING SYSTEMS AND BRACKETS



14615

## SWING OUT WALL RACKS

The swing out wall rack arrives ready to square and keyholes mount in minutes. Reinforcement plates stabilize the frame to allow maximum load bearing capacity. Hub and LAN applications are easily accommodated without door deflection. Latch pins or bolts secure the door to the frame and remove to swing open smoothly from the left or right.

### FEATURES:

- Opens to allow easy access to terminations without disturbing terminations
- Both latch pins and bolts are included
- Hook and loop straps feed into slots for backside cable management
- Side panels fold flat for shipping, then unfold for easy on-site assembly
- 5/8", 5/8", 1/2" universal mounting hole pattern
- Mounting holes threaded for #12-24 hardware
- Includes cross-recessed #12-24 black panel mounting screws
- Made of steel
- Meets EIA-310 standards
- Listed to the UL 1863 Standard for Communications Circuit Accessories

## SWING OUT WALL RACKS

Part Number	Description
14615	11U Swing Out Wall Mount Open Frame Rack - 18in Deep – 21"H x 19.75"W x 18"D, Load Rating: 75 lbs.
14616	19U Swing Out Wall Mount Open Frame Rack - 18in Deep – 35"H x 19.75"W x 18"D, Load Rating: 75 lbs.
14617	11U Swing Out Wall Mount Open Frame Rack - 25in Deep – 21"H x 19.75"W x 25"D, Load Rating: 75 lbs.

Notes: Black finish. Load rating based on using swing feature. Load increases when fixed.

Follow Us



# WALL MOUNT RACKS AND BRACKETS

## STANDARD EIA WALL MOUNT RACKING SYSTEMS



14618

Wall mount racks and hinged wall mount brackets are designed for applications where space is critical. Their wall mount design increases closet wiring capacity while allowing rear access to patch panels and equipment.

### WALL MOUNT RACKS

Wall mount racks offer the flexibility of an 18" (457mm) deep wall mounted unit for mounting telecommunications and data equipment. They are available in two heights, with front swing gates and 19" #12-24 threaded EIA pattern.

Part Number	Description
14618	12U Wall Mount Open Frame Rack - 18in Deep – 26"H x 20.25"W x 18"D, Load Rating: 75 lbs.
14619	25U Wall Mount Open Frame Rack - 18in Deep – 50"H x 20.25"W x 18"D, Load Rating: 125 lbs.

Notes: Fully assembled, supplied with 10 self-adhesive saddles and (12) 6" hook and loop straps.

### WALL MOUNT RACKS FIXED

Fixed wall mount racks offer the flexibility of either a 12" or 18" deep wall mounted unit for mounting 19" telecommunications and data equipment. They are available in three heights with #12-24 threaded EIA rails.



14610

Part Number	Description
14609	8U Wall Mount Open Frame Rack - 12in Deep – 17.75"H X 19.78"W X 12"D, Load Rating: 200 lbs.
14610	15U Wall Mount Open Frame Rack - 12in Deep – 30"H X 19.78"W X 12"D, Load Rating: 200 lbs.
14611	30U Wall Mount Open Frame Rack - 12in Deep – 56.25"H X 19.78"W X 12"D, Load Rating: 175 lbs.
14612	8U Wall Mount Open Frame Rack - 18in Deep – 17.75"H X 19.78"W X 18"D, Load Rating: 150 lbs.
14613	15U Wall Mount Open Frame Rack - 18in Deep – 30"H X 19.78"W X 18"D, Load Rating: 150 lbs.
14614	30U Wall Mount Open Frame Rack - 18in Deep – 56.25"H X 19.78"W X 18"D, Load Rating: 125 lbs.

Notes: Assembly required. Supplied with Fifty #12-24 mounting screws.

Follow Us



# WALL MOUNT RACKS AND BRACKETS

## STANDARD EIA WALL MOUNT BRACKETS



14620



14621



14625

### HINGED WALL MOUNT BRACKETS

Hinged wall mount brackets meet smaller system requirements and allow easy access to the rear of the panels. Holes in back allow for rear cable feed through. These brackets are available in three heights, with 19" #12-24 threaded EIA pattern. Fully assembled.

Part Number	Description
14620	2Ux19in Hinged Wall Mount Bracket – 3.5"H x 19"W x 6"D
14621	3Ux19in Hinged Wall Mount Bracket – 5.25"H x 19"W x 6"D
14622	4Ux19in Hinged Wall Mount Bracket – 7"H x 19"W x 6"D

### VERTICAL WALL MOUNT BRACKETS

Vertical wall mount brackets provide the ability to mount up to four rack units of equipment vertically on a wall. The innovative design also allows the brackets to be mounted to a 19" rack, under a work surface or even under Cablofil tray with optional hardware. The 3/8" square holes and installed #12-24 RU nuts allow patch panels, switches or even servers to be mounted to the brackets.

Part Number	Description
14623	2Ux19in Vertical Wall Mount Bracket – 20.25"W x 4.58"D x 6"H Load Rating: 200 lbs.
14624	3Ux19in Vertical Wall Mount Bracket – 20.25"W x 6.35"D x 6"H Load Rating: 200 lbs.
14625	4Ux19in Vertical Wall Mount Bracket – 20.25"W x 8.10"D x 6"H Load Rating: 200 lbs.

Notes: Supplied with Four #12-24 screws per rack unit and Ten 6" hook and loop fasteners.

Follow Us

