



## TruLink® HDMI and VGA Over Cat5 Series

- HDMI and VGA signal extension up to 300ft at 1920x1080 or 1920x1200 video resolutions
- TruChoice™ power allows the system to be powered from a single power supply at either the transmitter or receiver\*
- TruPair™ technology allows the system to function with any display on the market
- Plug & play operation



# Specifications: TruLink® HDMI and VGA Over Cat5 Series

## Signal Specifications:

---

Video Signal Support:	HDMI & VGA
Maximum Video Resolution:	1920x1080 or 1920x1200
Maximum Cable Distance:	300ft*
Recommended Category Cable:	Solid Cat5e or Cat6*

\*Solid conductor Cat5 or Cat6 cabling is recommended for use with the digital products, HDMI and HDMI with RS232. Coiling of excess cable lengths should be avoided for best performance results. Shielded, solid conductor Cat5 or Cat6 cabling is recommended if a cable must be coiled or is run near other high-frequency signaling cables.

## Power Adapter Specifications:

---

Input Voltage:	100-240V
Output Voltage/Amperage:	18V, 1.0A
Cable Length:	1.5m
Plug Diameter:	4.75mm
Center Pin Polarity:	Positive

## Physical Characteristics:

---

Video Input/Output Port:	HDMI Female, HD15 VGA Female
Data Input/Output Ports:	RJ45 Female x 2

Part Number	Description	Weight (lbs)
29296	TruLink Dual Gang HDMI + VGA Over Cat5 Transmitter—Aluminum	
29297	TruLink Dual Gang HDMI + VGA Over Cat5 Transmitter—White	
29212	TruLink HDMI + VGA over Cat5 Wall Plate Transmitter—Aluminum to Box Receivers Kit	
29213	TruLink HDMI + VGA over Cat5 Wall Plate Transmitter—White to Box Receivers Kit	

