



TruLink® VGA, Audio, Composite Video and HDMI Over Cat5 Series

- VGA, Audio, Composite Video and HDMI signal extension up to 300ft at 1920x1080 or 1920x1200 video resolutions
- Available in White & Aluminum Wall Plate options
- TruChoice™ power allows the system to be powered from a single power supply at either the transmitter or receiver*
- TruPair™ technology allows the system to function with any display on the market
- Plug & play operation



Specifications: TruLink® VGA, Audio, Composite Video and HDMI Over Cat5 Series

Signal Specifications:

Video Signal Support:	VGA, Composite Video, HDMI
Audio Signal Support:	Stereo Audio x 2 (3.5mm and Left and Right RCA)
Maximum Video Resolution:	1920x1080 or 1920x1200
Maximum Cable Distance:	300ft
Recommended Category Cable:	Solid Cat5e or Cat6*

*Solid conductor Cat5 or Cat6 cabling is recommended for use with the digital products, HDMI and HDMI with RS232. Coiling of excess cable lengths should be avoided for best performance results. Shielded, solid conductor Cat5 or Cat6 cabling is recommended if a cable must be coiled or is run near other high-frequency signaling cables.

Power Adapter Specifications:

Input Voltage:	100-240V
Output Voltage/Amperage:	18V, 1.0A
Cable Length:	1.5m
Plug Diameter:	4.75mm
Center Pin Polarity:	Positive

Physical Characteristics:

29231-2		29265-6	
Video Ports:	HDMI Female x 1 HD15 Female x 1 RCA Female x 1	Video Ports:	HDMI Female x 1 HD15 Female x 1 RCA Female x 1
Audio Ports:	3.5mm Female x 1 RCA x 2	Audio Ports:	3.5mm Female x 1 RCA x 2
Data Ports:	RJ45 Female x 2	Data Ports:	RJ45 Female x 2
Enclosure Material:	Aluminum	Wall Plate Material:	Aluminum
Dimensions:	10 x 10 x 4.9cm	Dimensions:	10.4 x 5.5 x 4.9cm

Part Number	Description
29231	TruLink VGA, Audio, Composite Video, and HDMI over Cat5 Dual Gang Wall Plate Transmitter - Aluminum
29232	TruLink VGA, Audio, Composite Video, and HDMI over Cat5 Dual Gang Wall Plate Transmitter - White

