

SPECIFICATION SHEET



IB-4X Infiniband Latching Cable

- Assembled with 26AWG cable
- Support for 10GB data speeds
- TAA Compliant
- Lifetime warranty

Specifications: IB-4X Infiniband Latching Cable

Electrical characteristics:

Differential impedance:	100 ± 5Ω
Mutual capacitance:	14pF/ft nominal
Time delay:	1.35ns/ft nominal
Time delay skew (within pairs):	120ps/9m maximum
Time delay skew (between pairs):	500ps/9m maximum
Attenuation:	10dB/9m @1.25GHz
Conductor DC Resistance:	0.040Ω/ft nominal @ 20°C

Physical specifications:

Conductors (eight pair):	26AWG Solid Silver plated copper
Insulation:	Foam polyolefin
Pair drain wire:	30AWG Solid Solid silver plated copper
Pair shield:	Aluminum polyester tape 125% coverage
Overall cable shield:	Aluminum polyester tape 125% coverage Tin plated copper braid 38AWG, 85% coverage
Outer diameter:	0.345in

Connector specifications:

Connector type:	SFF-8470
-----------------	----------

Part Number	Description	Weight (lb)
33067	7m IB-4X Infiniband Latching Cable	1.94



CABLES TO GO

Cables To Go
3555 Kettering Blvd.
Moraine, OH 45439
Phone: 800.287.2843
www.c2g.com

Follow Us

