

SPECIFICATION SHEET



10G CX4 Latching Cable

- Assembled with 28AWG cable
- Support for 10GB data speeds
- RoHS Compliant
- TAA compliant
- Lifetime warranty

Specifications: 10G CX4 Latching Cable

Electrical characteristics:

Differential impedance:	100 ± 5Ω
Mutual capacitance:	14pF/ft nominal
Time delay:	1.35ns/ft nominal
Time delay skew (within pairs):	120ps/7m maximum
Time delay skew (between pairs):	500ps/7m maximum
Attenuation:	10dB/7m @1.25GHz
Conductor DC Resistance:	0.066Ω/ft nominal @ 20°C

Physical specifications:

Conductors (eight pair):	28AWG Solid Silver plated copper
Insulation:	Foam polyolefin
Pair drain wire:	30AWG Solid Solid silver plated copper
Pair shield:	Aluminum polyester tape 125% coverage
Overall cable shield:	Aluminum polyester tape 125% coverage Tin plated copper braid 38AWG, 85% coverage
Outer diameter:	0.185in

Connector specifications:

Connector type:	SFF-8470
-----------------	----------

Part Number	Description	Weight (lb)
33070	0.5m 10G-CX4 Latching Cable	0.32
33071	1m 10G-CX4 Latching Cable	0.42
33072	3m 10G-CX4 Latching Cable	0.8
33073	5m 10G-CX4 Latching Cable	0.91
33074	7m 10G-CX4 Latching Cable	1.02



CABLES TO GO

Cables To Go
3555 Kettering Blvd.
Moraine, OH 45439
Phone: 800.287.2843
www.c2g.com

Follow Us

